

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 135- 22,514 -0000

SW SW NW, Sec. 32, T 20 S, R 24 W/X

330 feet from N/S section line

330 feet from W/X section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5097

Lease Name Neuforth Well # 1

Operator: Martin Oil Producers, Inc.
Name & 1010 Union Center
Address Wichita, KS 67202

County Ness

Well Total Depth 4490 feet 145.92

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 510

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Kaw Drilling Co., Inc. License Number 6739

Address 1010 Union Center, Wichita, KS 67202

Company to plug at: Hour: 5:00 pm Day: 30 Month: January Year: 19 84

VERBAL PLUGGING ORDERS GIVEN TO Lyle Juergenson

(company name) Kaw (phone) 316-264-0316

were: to fill hole with heavy mud and spot cement through drill pipe.

1st plug at 1590' with 50 sx cement

2nd plug at 780' with 60 sx cement
solid bridge

3rd plug hulls - plug at 40' -- cement to surface with 10 sx cement.

5th plug to circulate rat hole with 15 sx cement.

Signed *[Signature]*
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 7:00 pm Day: 30 Month: January Year: 19 84

ACTUAL PLUGGING REPORT 1st plug at 1590' with 50 sx cement, 2nd plug at 780' with 60 sx cement, 3rd plug solid bridge - hulls - plug at 40' -- cement to surface with 10 sx cement. Circulate rat hole with 15 sx cement.

Remarks: Use 60/40 Pozmix 2% gel, 3% cc. by Halliburton

RECEIVED
STATE CORPORATION COMMISSION
FEB 02 1984
CONSERVATION DIVISION
Wichita, Kansas

I hereby certify that the above plugging instructions were given as herein stated and that I (~~xxx~~ / did not) observe this plugging.

INDEXED
DATE 2-3-84
INDEX 0046

Signed *[Signature]*
(TECHNICIAN)