

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-207 20,074-0000

NWSE SW, Sec. 18, T 19 S, R 37 W/2

990 feet from ~~W~~/S section line

1500 feet from W/~~W~~ section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 7264

Lease Name Fairchild Well # 1

Operator: Westburne Petroleum Inc  
Name & Address: 999 18th Ste 308  
Denver, Colorado 80202

County Wichita

Well Total Depth 6321 feet 200.43

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 430

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Sage Drilling Co Inc License Number 5421

Address 202 S. St Francis Wichita KS 67202

Company to plug at: Hour: 12:00 midnight Day: 29 Month: October Year: 1983

VERBAL PLUGGING ORDERS GIVEN TO Bill Luck

(company name) Westburne Petroleum (phone) \_\_\_\_\_

were: To use 60/40 pozmix 2% gel 3% cc  
1st plug @ 2300' w/50sx, ~~1st~~ 2nd plug  
@ 1320' w/50sx, 3rd plug @ 480' w/40sx,  
4th plug @ 40' w/solid Bridge plug + 10sx,  
Circulate 10sx in the Rathole Circulate 10sx  
in the mousehole

Signed Richard W. Lacey  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 4:45 am Day: 29 Month: October Year: 1983

ACTUAL PLUGGING REPORT Plugged as proposed in above paragraph  
Sun oil well cementing pumped the cement

Remarks: \_\_\_\_\_

I hereby certify that the above plugging instructions were given as herein stated  
and that I (did / did not) observe this plugging.

INVOICED

DATE 11-15-83 RECEIVED STATE CORPORATION COMMISSION

INV. NO. 6081-6 NOV 2 1983  
11-2-83  
CONSERVATION DIVISION  
Wichita, Kansas

Signed Richard W. Lacey  
(TECHNICIAN)