

1031284

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

6-25

API NUMBER 15- 203-20,110-0000
NW NW SW, SEC. 7, T. 20 S, R. 35 W
2310 feet from S section line
330 feet from WE section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5506

Lease Name W.R. Wells Well # 1

Operator: Woolsey Petroleum Corp.

County Wichita

Name & Address 107 N. Market, Ste. 600

Well Total Depth 5250 170.62 feet

Wichita, KS 67202-1807

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 211

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A

Other well as hereinafter indicated _____

Plugging Contractor Abercrombie RTD, Inc. License Number 30684

Address 150 N. Main, Ste. 801, Wichita, KS 67202-1383

Company to plug at: Hour: _____ Day: 25 Month: 6 Year: 19 94

Plugging proposal received from Gary Fisher

(company name) Abercrombie RTD, Inc. (phone) 316-262-1841

was: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2283-99'

1st plug at 2300' with 50 sx cement, 2nd plug at 1250' with 80 sx cement,

3rd plug at 720' with 40 sx cement, 4th plug at 220' with 40 sx cement,

5th plug at 40-0' with 10 sx cement,

6th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Steve Durrant (TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None

Operations Completed: Hour: 10 p.m. Day: 25 Month: 6 Year: 19 94

ACTUAL PLUGGING REPORT 1st plug at 2300' with 50 sx cement,

2nd plug at 1250' with 80 sx cement,

3rd plug at 720' with 40 sx cement,

4th plug at 220' with 40 sx cement,

5th plug at 40-0' with 10 sx cement,

6th plug to circulate rathole with 15 sx cement.

Remarks: Used 60/40 Pozmix 6% gel 1/2# floseal by Allied.

If additional description is necessary, use BACK of this form.

INVOICED

DATE JUL 07 1994

INV. NO. 40788

6-25

Signed Steve Durrant (TECHNICIAN)

RECEIVED STATE CORPORATION COMMISSION JUN 29 1994 CONSERVATION DIVISION Wichita, Kansas