٠, TO:

STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING

130 SOUTH MARKET, SUITE 2078

WICHITA, KANSAS 67202

Operator License No.: 4894

Op Name: HORSESHOE OPERATING, INC.

Address: 500 W. TEXAS, STE 1190

Proposal Revd. from: DAVE OLSON

MIDLAND, TX 79701

API Well Number: 15-071-20125-00-00

Sec/Twnshp/Rge: 21-20S-40W Spot: NWNWNWSE

2340 feet from S Section Line, 2340 feet from E Section Line

Lease/Unit Name: KING L

Well Number: 1

Total Vertical Depth: 2929 feet County: GREELEY

Conductor Pipe: Size

feet:

Surface Casing: Size 8.625

feet: 411

WITH 185 SX CMT

Production: Size 4.5

Company: HORSESHOE OPERATING

feet: 2924

WITH 250 SX CMT

Liner: Size

feet:

Well Type: GAS

UIC Docket No:

Date/Time to Plug: 05/14/2002 11:45 AM

Plug Co. License No.: 99996

Plug Co. Name: ALLIED CEMENT COMPANY

Phone: (915) 683-1448

Proposed PUMP 400# HULLS& 20 SX CMT. PRESSURE UP TO 500#. PERFORATE AT 1350'. PUMP 80 SX CMT OVER

Plugging CASING CAPACITY. PUMP 150 SX CMT DOWN 8 5/8" X 4 1/2" ANNULUS.

Method:

Plugging Proposal Received By: KEVIN STRUBE


WitnessType: Plugging Operations 100% Witnessed (Complete)

Date/Time Plugging Completed: 05/14/2002 6:00 PM

KCC Agent: KEVIN STRUBE

Actual Plugging Report:

PBTD 2924'. PERFS AT 2811-15'. PUMPED DOWN 4 1/2" 400# HULLS & 20 SX CMT DISPLACED TO 2600'. WOULD NOT HOLD. PUMPED 200# HULLS & 50 SX CMT. DISPLACED TO 1800'. PRESSURED UP TO 1000#. PERFORATED AT 1350'. PUMPED DOWN 4 1/2" 160 SX CMT. MAXIMUM PRESSURE 1000#. SHUT IN AT 500#. PUMPED DOWN 8 5/8" X 4 1/2" ANNULUS 50 SX CMT. MAXIMUM PRESSURE 200#. SHUT IN AT 0#. ANNULUS STAYED LOADED STARTED PUMPING CMT AROUND BACK SIDE OF SURFACE.



USED 60/40 POZMIX 6% GEL BY ALLIED. NO CASING RECOVERED. Remarks:

Plugged through: CSG

District: 01

Signed Kown D Struke (TECHNICIAN)

MAY 1 5 2002

