

1060125

TO: STATE CORPORATION COMMISSION

API NUMBER 15-165-21,685-0000
C SW NE SEC. 3, T 16 S, R 18 W

10-9

CONSERVATION DIVISION - PLUGGING SECTION 3300 FEET FROM SOUTH SECTION LINE

WICHITA STATE OFFICE BLDG., 130 S. MARKET 1980 FEET FROM EAST SECTION LINE

WICHITA, KANSAS 67202

LEASE NAME HERL TRUST WELL # 2

TECHNICIAN'S PLUGGING REPORT

COUNTY RUSH 117.88

OPERATOR LICENSE # 31741

WELL TOTAL DEPTH 3627 FEET

OPERATOR: LIBOC, INC

PRODUCTION CSG: SIZE 5 1/2 " FEET 3627

NAME AND 16430 PARK TEN PL DR, STE 600

SURFACE CASING: SIZE 8 3/8 " FEET 1102'

ADDRESS HOUSTON, TX 77084

ABANDONED OIL WELL GAS WELL INPUT WELL SWD WELL D/A

OTHER WELL AS HEREINAFTER INDICATED _____

PLUGGING CONTRACTOR DS&W WELL SERVICING LICENSE NUMBER 6901

ADDRESS PO BOX 231 CLAFLIN, KS 67525

COMPANY TO PLUG AT: HOUR: 10:30 AM DAY: 09 MONTH: 10 YEAR: 1998

PLUGGING PROPOSAL RECEIVED FROM KENT

(COMPANY NAME) DS&W (PHONE) 316-587-3361

WERE: PERFS AT 3495-3498

1ST PLUG PUMP 25 SX CEMENT TO BOTTOM,

2ND PLUG AT 1130' WITH 50 SX CEMENT,

3RD PLUG AT 550' WITH 40 SX CEMENT.

4TH PLUG AT 40' WITH 10 SX CEMENT.

PLUGGING PROPOSAL RECEIVED BY MIKE MAIER

PLUGGING OPERATIONS ATTENDED BY AGENT?: ALL PART _____ NONE _____

OPERATIONS COMPLETED: HOUR: 12:00 PM DAY: 09 MONTH: 10 YEAR: 1998

ACTUAL PLUGGING REPORT _____

1ST PLUG PUMPED 25 SX OF COMMON CEMENT TO BOTTOM,

2ND PLUG AT 1130' WITH 50 SX CEMENT,

3RD PLUG AT 550' WITH 40 SX CEMENT.

4TH PLUG AT 40' WITH 10 SX CEMENT.

REMARKS: 60/40 POZMIX 6% GEL BY ALLIED. RECOVERED 2300' OF 5 1/2" CASING

(IF ADDITIONAL DESCRIPTION IS NECESSARY, USE BACK OF THIS FORM.)

I (DID) OBSERVE THIS PLUGGING.

SIGNED Michael J. Maier
(TECHNICIAN) FORM CP-2/3

12-19-98
60118