

To: 1 071012  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

12-9  
API NUMBER 15- 101-20,597-6000  
100' SE of 97  
NE NW SW, SEC. 13, T. 16 S, R. 30 W/E

TECHNICIAN'S PLUGGING REPORT

Operator License # 5151

Operator: Gear Petroleum Co., Inc.  
Name &  
Address 125 N. Market, Suite 1075  
Wichita, KS 67202-1710

2260 feet from S section line

4250 feet from E section line

Lease Name D.E. Roemer A Well # 2

County Lane 143.35

Well Total Depth 4411 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 327

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Gear Petroleum Co. License Number 5151

Address 125 N. Market, Suite 1075, Wichita, KS 67202-1710

Company to plug at: Hour: 11:20 a.m. Day: 9 Month: 12 Year: 19 91

Plugging proposal received from Bill Hammack

(company name) Gear Petroleum Co. (phone) 316-265-3351

were: 4 1/2" at 4400' w/175 sx cement, Perfs at 4278-32', Open hole 4400-11', 2-staged  
2215-0' w/500 sx cer

1st plug pump 500 lbs. hulls in first part of 140 sx Econolight cement down 4 1/2"

Check backside.

Plugging Proposal Received by Dan Goodrow  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 11:40 a.m. Day: 9 Month: 12 Year: 19 91

ACTUAL PLUGGING REPORT 1st plug pumped 500 lbs. hulls in first part of 140 sx Econolight  
cement down 4 1/2". Maximum pressure 1100 psi and shut in 1000 psi.

Backside would not take.

Remarks: Used Econolight cement by Halliburton. No casing recovery.

(If additional description is necessary, use BACK of this form.)

**INVOICED**

**RECEIVED**

(If additional description is necessary, use BACK of this form.)  
STATE CORPORATION COMMISSION

DATE 1-7-92

INV. NO. 34211

12-8-91  
CONSERVATION DIVISION  
WICHITA, KANSAS

Signed Dan Goodrow  
(TECHNICIAN)