

1 070472

11-23-87

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-101-20,815-0000  
SE NW NE, SEC. 35, T 16 S, R 30 W/EX

TECHNICIAN'S PLUGGING REPORT

Operator License # 5151

4290 feet from S section line  
1650 feet from E section line

Operator: Gear Petroleum Company, Inc.  
Name & Address 1075 KSB Building, 125 N. Market  
Wichita, KS 67202

Lease Name Harper Well # 1-35  
County Lane 151.13  
Well Total Depth 4650 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 289

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Gear Petroleum Company, Inc. License Number 5151  
Address 1075 KSB Building, 125 North Market, Wichita, KS 67202

Company to plug at: Hour: 10:45 a.m. Day: 23 Month: 11 Year: 19 87

Plugging proposal received from Max Parsons  
(company name) Gear Petroleum Company, Inc. (phone) 913-628-6904

were: 4 1/2" at 4641' PRTD 4150' Perfs at 4552-57, 4124-28'

1st plug DV from 1232-0'

2nd plug pump 4 sx hulls and enough ATL cement to fill hole down the 4 1/2" production casing.

Plugging Proposal Received by Richard Lacey  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 11:15 a.m. Day: 23 Month: 11 Year: 19 87

ACTUAL PLUGGING REPORT DV at 1232', cement to 425'.

1st plug pumped 200 sx 60/40 Pozmix down 8 5/8".

2nd plug pumped 500 lbs. hulls and 93 sx ATL cement down 4 1/2" casing.

Maximum pressure 1500 psi and shut in 1400 psi.

Remarks: Used 60/40 Pozmix and ATL cement by Allied. No casing recovery.  
(if additional description is necessary, use BACK of this form.)

INVOICED (observe this plugging.)

Signed Dan Dodson  
(TECHNICIAN)

DATE 12-2-87

INV. NO. 19026-11 23

NOV 25 1987  
WICHITA