1080086

To:	API NUMBER 15- 165-21,162.
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING	NS , Sec. 35 , T 16 S, R 18 WXX
WICHITA, KANSAS 67202	feet from N/SX section line
TECHNICIAN'S PLUGGING REPORT	feet from W/XX section line
Operator License # 5140	Lease Name Schaffer Well # 1
Operator: Frontier Oil Company Name & 1720 Kansas State Bank Building Address Wichita, KS 67202	CountyRush
	Well Total Depth 3670 feet 119.27
•	Conductor Pipe: Sizefeet
	Surface Casing: Size 8 5/8 feet 1189
Abandoned Oil Well Gas Well Inpu	it Well SWD Well D&A X
Other well as hereinafter indicated	
Plugging Contractor Red Tiger Drilling Co.	
Address 1720 Kansas State Bank Building, W	
Company to plug at: Hour: 12:00 am Day: 5	Month: February Year:19 84
VERBAL PLUGGING ORDERS GIVEN TO Ross Craw	ford
(company name) Red Tiger	(phone) 316-263-2371
were: to fill hole with heavy mud and	spot cement through drill pipe.
st plug at 1200' with 50 sx cement	
2nd plug at 600' with 40 sx cement	
solid bridge 3rd plug hulls - plug at 40' cement tosur:	face with 10 sx cement.
5th plug to circulate rathole with 15 sx ceme	ent.
	Signed 1 M Thus
4	(TECHNIZIAN)
Plugging Operations attended by Agent?: All_	
Operations Completed: Hour: 4:00 am Day:	5 Month: February Year:19 84
ACTUAL PLUGGING REPORT 1st plug at 1200	with 50 sx cement, 2nd plug at 600' with
40 sx cement, 3rd & 4th plugs - solid bridge	
with 10 sx cement. 5th plug to circulate rate	chole with 15 sx cement.
Remarks: Use 60/40 Pozmix with 2% gel, 3%	occ. by Allied.
Remarks: Use 60/40 Fozmix With 2% gel, 3%	
	·
I hereby certify that the above plugging	instructions were given as herein stated
and that I (A / did not) observe this pluggi	ing.
RECEIVED STATE CORPORATION COMMISSION 2-13-80	Signed 1 11 727
STATE CORPORATION COMMISSION	(TECHNICIAN)

CONSERVATION DIVISION Wighita, Kansas

FEB 0 8 1984

٦ - 🤇

FORM CP-2/3 Rev. 9-82