SIDE ONE	V Company tion Comp
Two (2) copies of this form shall be filed with mission, 200 Colorado Derby Building, Wichita, Kansa days after the completion of a well, regardless of heat Attach separate letter of request if the inform If confidential, only file one copy. Information on	ow the well was completed. ation is to be held confidential.
and side Two will then be held contidential.	
Applications must be made on dual completion, c	ommingling, salt water disposal,
t townsmently shandaned wells	
None Attach one copy only wireline logs (i.e. electroneutron log, etc.). (Rules 82-2-105 & 82-2-125) KC	C# (316) 263-3238.
neutron log, etc.). (Rules 62-2-10) d 62 2 125) No	6-30-84
LICENSE # 6518 EXPIRATION DATE	APT NO. 15 051 02 912-00-00
OPERATOR Wamego Oil, Inc.	APT NO. 13-031,23,313-00-09
	COUNTY Ellis
Junction City, Kansas 66441	PROD FORMATION 4
** CONTACT PERSON Harold Sadowski PHONE 913-238-8954	-
PURCHASER None	LEASE Matilda Al port
ADDRESS	WELL NO. #6
	WELL LOCATION NE 1/4
DRILLING Pioneer Drilling Co.	330 Ft. from N Line and
CONTRACTOR	1980 Ft. from E Line of
ADDRESS Plainville, Kansas 67663	the NE (Qtr.)SEC 30TWP 11SRGE 19 (W)
The state of the s	WELL PLAT (Office
PLUGGING Pioneer Drilling Co. (Tom ALM) CONTRACTOR	Use Only)
ADDRESS 308 West Mill	KCC_V
Plainville, Kansas 67663	- SWD/REP
TOTAL DEPTH 3710' PBTD	- PLG.
SPUD DATE 3-09-84 DATE COMPLETED 3-15-84	_
ELEV: GR 2120' DF 2123' KB 2k25'	-
DRILLED WITHX KNAPLEX (ROTARY) XXIVXX TOOLS.	
DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE N/A	
Amount of surface pipe set and cemented 8 5/8" 8250	_DV Tool Used?N/A
THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil' Gas, Injection, Temporarily Abandoned, OWWO. Other	
ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULAT AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.	IONS PROMULGATED TO REGULATE THE OIL
	·
<u>AFFIDAVIT</u>	•
Harold Sadowski , b	eing of lawful age, hereby certifies
that: I am the Affiant, and I am familiar with the c	contents of the foregoing Affidavit.
The statements and allegations contained therein ar	
•	Tarl Solombi
	(Name)
SUBSCRIBED AND SWORD, TO BEFORE ME this ACH	day of (ANN),
1984. WONANTER	
NOTARY P	della MOY Vivia
PUBLIC My Appl. Exp.	(NOTARY PUBLIC)
MY COMMISSION EXPIRES: 2-23/2	,
THE AND THE PROPERTY OF THE PARTY OF THE PAR	
** The person who can have eached by phone regarding	g any questions concerning this
information.	any questions concerning this STATE CORPORATION COMMISSION CONSERVA
•	PORATIONED
	APR 2 2 COMMISS.
	APR 2 3 1984 CONSERVATION DIVISION Wichia Kansas
·	Wichita. Kansas
·	ansas Olon

ACO-1 WELL HISTORY

OPERATOR WAMEGO OIL, INC. LEASE

Allbert

FILL IN WELL LOG AS REQUIRED:

SEC. 30 TWP. 11S RGE. 19W

cluding 6	depth interval te								M4 4 4 4 P		DEP	
	FORMATION I	DESCRIPTION, CO	NTENTS, ETC.		ТОР	B0	TTOM		HAME		DEP	
	-					ì					,	
Anh	yorite				1487	15	530					
Top	oeka				3139	1						
	ebner	:			3356	١ .						
Tor	ronto			-	3376	1						
Lan	sing				3394	36	318					
	rmaton		·		3637	ļ						
	nglomera	ite			3670	1						
	al Dept					37	710					
	•											
			,									
					,							
	NO EL	ECTRIC I	<u>LOG</u>					Ì				
	De	t. #1										
	16' to 3											
	en 60 mi							ļ				
Rec	2. 10' s	slightly	oil sp	ecked mud								
1.8	₹.P 199	8#			'							
		33# (30)	•		1	j					1	
1						1		1				
2.1	I.P. 67	2# (30)	,		ļ			Ì			i	
F.H	H.P. 19	990#			}			1				
ì						1		1			1	
					1			1			ļ	
I												
			•								1	
			•									
		s set — surface,	Size casing to				<u>_</u>	ew) c	or (Use		ype and p	recent
Purpo	se of string	Size hole drilled	Size casing te (in O.D.)	Weight lbs/ft.	Setting depth	Тур	e cement	ew) c	Sacks	7	additive	
Purpo		Size hole drilled	Size casing to		Setting depth		e cement	ew) c			additive	3%
Purpo	se of string	Size hole drilled	Size casing te (in O.D.)	Weight lbs/ft.	Setting depth	Тур	e cement	ew) c	Sacks	7	additive	
Purpo	se of string	Size hole drilled	Size casing te (in O.D.)	Weight lbs/ft.	Setting depth	Тур	e cement	ew) c	Sacks	7	additive	
Purpo	se of string	Size hole drilled	Size casing se (in 0.0.)	Weight lbs/ft.	Setting depth	Тур	POS		Secks	2%	additive	
Purpo	Casing	Size hole drilled	Size casing section (in O.D.) 8 5/8"	Weight lbs/ft.	Setting depth	Тур	POS	ORAT	Sacks	2%	additive	3%.
Purpo	Casing	Sixe hole drilled 12½" LINER RECO	Size casing section (in O.D.) 8 5/8"	weight lbs/ff. 20#	Setting depth	Тур 60-40	POS	ORAT	Secks 150	2%	GEL	3%.
Purpo face	Casing	Size hole drilled 12点" LINER RECO	Size casing se (in O.D.) 8 5/8** RD NO Secks	Weight Ibs/H. 20#	Setting depth	Тур 60-40	POS	ORAT	Secks 150	2%	GEL	3%.
Purpo	Casing	Sixe hole drilled 12½ '' LINER RECO	Size casing se (in O.D.) 8 5/8** RD NO Secks	weight lbs/ff. 20#	Setting depth	Тур 60-40	POS	ORAT	Secks 150	2%	GEL	3%.
Purpo face	Casing	LINER RECO	Size casing se (in O.D.) 8 5/8** RD NO Secks ORD Packs ACID, FRAC	Weight Ibs/H. 20# Piecement Ture, Shot,	Setting depth 2591	60-40	PERF	ORAT	Secks 150	2% ORD	GEI	3%
Purpo face	Casing	LINER RECO	Size casing se (in O.D.) 8 5/8** RD NO Secks ORD Packs ACID, FRAC	Weight lbs/ff. 20#	Setting depth 2591	60-40	PERF	ORAT	Secks 150	2% ORD	GEL	3%
Purpo face	Casing	LINER RECO	Size casing se (in O.D.) 8 5/8** RD NO Secks ORD Packs ACID, FRAC	Weight Ibs/H. 20# Die cement TURE, SHOT, of material used	Setting depth 2591	60-40	PERF	ORAT	Secks 150	2% ORD	GEI	3%
Purpo face	Casing	LINER RECO	RD NO Socks ACID, FRAC	Weight Ibs/H. 20# Die cement TURE, SHOT, of material used	Setting depth 2591	60-40	PERF	ORAT	Secks 150	2% ORD	None Depth Into	3 %
Purporface Top, ft.	Casing	LINER RECO	Size casing section (in O.D.) 8 5/811 RD No Socks ORD Packs ACID, FRAC	Weight Ibs/H. 20# Die cement TURE, SHOT, of material used	Setting depth 2591 Short	GO-40	PERI	ORAT	Secks 150 SON REC	2%	None Depth Into	3 %
Purporface Top, ft.	Casing Birst production	LINER RECO	Size casing section (in O.D.) 8 5/811 RD No Socks ORD Packs ACID, FRAC	Weight lbs/ff. 20# 20# Die cement TURE, SHOT, of material used Compared to the compared t	Setting depth 2591 Short	GO-40	PERF	ORAT	Secks 150	2%	None Depth Inte	3 %
Purpor face Top, ft.	Casing Birst production	LINER RECO	Size casing section (in O.D.) 8 5/8** RD NC Secks ORD Packs ACID, FRAC	weight lbs/ff. 20# 20# Price cement TURE, SHOT, of material used	Setting depth 2591 Short	GO-40	PERI	ORAT	Secks 150 SON REC	2% ORD Depth int	None Depth Inte	3 %