

STATE OF KANSAS
STATE CORPORATION COMMISSION
200 Colorado Derby Building
Wichita, Kansas 67202

WELL PLUGGING RECORD
K.A.R.-82-3-117

API NUMBER 15-101-21,469-0000

LEASE NAME JOHN SNIDER

WELL NUMBER 1-36

2310 Ft. from S Section Line

1650 Ft. from E Section Line

SEC. 36 TWP. 16 RGE. 30 (X) or (W)

COUNTY LANE

Date Well Completed 6-4-88

Plugging Commenced 6-4-88

Plugging Completed 6-4-88

TYPE OR PRINT
NOTICE: Fill out completely
and return to Cons. Div.
office within 30 days.

LEASE OPERATOR GALLOWAY PETROLEUM EXPLORATION INC.

ADDRESS 360 BROADWAY PLAZA BLDG., WICHITA, KS 67202

PHONE# (316) 267-7355 OPERATORS LICENSE NO. 4661

Character of Well _____

(Oil, Gas, D&A, SWD, Input, Water Supply Well)

Did you notify the KCC/KDHE Joint District Office prior to plugging this well? _____

Which KCC/KDHE Joint Office did you notify? DODGE CITY, MR. LUTHI

Is ACO-1 filed? YES If not, is well log attached? _____

Producing Formation _____ Depth to Top _____ Bottom _____ T.D. 4590'

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Formation	Content	From	To	Size	Put in	Pulled out
<u>SURFACE</u>		<u>0</u>	<u>367'</u>	<u>8 5/8</u>	<u>367'</u>	<u>0</u>

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from ___ feet to ___ feet each set.

50 SX @ 2260'; 80 SX @ 1350'; 50 SX @ 360'; 10 SX @ 40'; 15 SX IN RAT HOLE

ALL CEMENT 60/40 POZ, 6% GEL 205 SX TOTAL

(If additional description is necessary, use BACK of this form.)

Name of Plugging Contractor GALLOWAY DRILLING CO., INC. License No. 5783

Address 340 BROADWAY PLAZA BLDG., WICHITA, KS 67202

STATE OF KANSAS COUNTY OF SEDGWICK, ss.

(Employee of Operator) or (Operator) of above-described well, being first duly sworn on oath, says: That I have knowledge of the facts stated herein and the log of the above-described well as filed that the same are true and correct, so help me God.

(Signature) _____

(Address) _____

RECEIVED
STATE CORPORATION COMMISSION
7-29-88
JUL 29 1988

CONSERVATION DIVISION
Wichita, Kansas

Subscribed and sworn to before me this 28th day of July, 19 88

Traci R. Landin
Notary Public

My Commission Expires: March 31, 1992



NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date 5 10 88 month day year

API Number 15-101-21,469-0000

OPERATOR: License # 4661 Name GALLOWAY PETROLEUM EXPLORATION, INC. Address 360 BROADWAY PLAZA BLDG, City/State/Zip WICHITA, KS 67202 Contact Person CASEY GALLOWAY Phone (316) 267-7355

NE. NW. SE. Sec. 36 Twp. 16 S, Rg. 30 East 2310 West 1650 Ft. from South Line of Section Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

Nearest lease or unit boundary line 330 feet County LANE

CONTRACTOR: License # 5783 Name GALLOWAY DRILLING CO., INC. City/State WICHITA, KS 67202

Lease Name JOHN SNIDER Well # 1-36

Well Drilled For: X Oil SWD Infield Mud Rotary Gas Inj X Pool Ext Air Rotary OWWO Expl Wildcat Cable

Ground surface elevation NA feet MSL Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no

Depth to bottom of fresh water 250' Depth to bottom of usable water 1100' 1300'

Surface pipe by Alternate: 1-2 X

Surface pipe planned to be set 350' Conductor pipe required

Projected Total Depth 4650 feet

Formation MISSISSIPPI

If OWWO: old well info as follows:

Operator Well Name Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

Date 04-20-88 Signature of Operator or Agent Casey F. Galloway Title PRESIDENT

For KCC Use:

Conductor Pipe Required feet; Minimum Surface Pipe Required 270 feet per Alt. 1 X

This Authorization Expires 10-21-88 Approved By RCH 4/21/88

EFFECTIVE DATE: 4-26-88 Move in 5:26.88 E Spud 350 894

NE. NW. SE. Sec. 36 Twp. 16 S, Rg. 30 East X West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 2000 feet depth with 50 60/40 POZ
2nd plug @ 1300 feet depth with 50 60/40 POZ
3rd plug @ 350 feet depth with 10 60/40 POZ
4th plug @ 40 feet depth with 10 60/40 POZ
5th plug @ 10 feet depth with 10 60/40 POZ
(2) Rathole with 10 (b) Mousehole with

PUSHER Carl Blair TD 4590 FORMATION MISS SURFACE PIPE 8 3/4 @ 360 ANHYDRITE 2361 ELEVATION STARTING TIME & DATE 4:30-PM. COMPLETION TIME & DATE 6:50 PM 6-4-88 1st PLUG @ 2260 FT. W/ 50 SX 2nd PLUG @ 1350 FT. W/ 40 SX 3rd PLUG @ 360 FT. W/ 50 SX 4th PLUG @ 40 FT. W/ 10 SX RAT HOLE CIRCULATED W/ 15 SX MOUSE HOLE CIRCULATED W/ SX WATER WELL PLUGGED W/ 40 SX CEMENT COMPANY FILLCO 614670 TECHNICIAN GRB

RECEIVED STATE CORPORATION COMMISSION

JUN - 8 1988

CONSERVATION DIVISION Wichita, Kansas