	•	
TYPE AFFIDAVIT OF COMPLETION FO	RM ACO-1 WELL HISTORY Compt.	
SIDE ONE	· · · · · · · · · · · · · · · · · · ·	
Two (2) copies of this form shall be filed with mission, 200 Colorado Derby Building, Wichita, Kansa days after the completion of a well, regardless of head that Attach separate letter of request if the information on the confidential, only file one copy. Information on record and Side Two will then be held confidential.  Applications must be made on dual completion, conjection and temporarily abandoned wells.	ow the well was completed. ation is to be held confidential. Side One will be of public ommingling, salt water disposal,	
Attach one copy only wireline logs (i.e. electroneutron log, etc.). (Rules 82-2-105 & 82-2-125) KC	ical log, sonic log, gamma ray C# (316) 263-3238.	
LICENSE # 5123 EXPIRATION DATE	· ·	
OPERATOR Pickrell Drilling Company	API NO. 15-057-20,289	
ADDRESS 110 N. Market, Suite 205	COUNTY Ford	
Wichita, Kansas 67202	FIELD Fager Pool	
** CONTACT PERSON <u>Jack Gurley</u> PHONE 262-8427	PROD. FORMATION Morrow	
PURCHASER Waiting on contract.	LEASE #1 Christian Church 'A'	
ADDRESS	WELL NO. 1	
	WELL LOCATION SE NW SW	
DRILLING Pickrell Drilling Company	1650 Ft. from South Line and	
CONTRACTOR ADDRESS 110 N. Market, Suite 205	990 Ft. from West Line of	
ADDRESS 110 N. Market, Suite 205 Wichita, Kansas 67202	the SW (Qtr.) SEC 36 TWP 29S RGE 25 (W).	
PLUGGING Pickrell Drilling Company	WELL PLAT (Office Use Only)/	
CONTRACTOR	KCC KCC	
ADDRESS 110 N. Market, Suite 205	KGS V	
Wichita, Kansas 67202	SWD/REP	
TOTAL DEPTH 5430' PBTD 12/1/92	PLG	
SPUD DATE 11/6/82 DATE COMPLETED 12/1/82	-	
ELEV: GR 2577 DF 2579 KB 2582		
DRILLED WITH (CASE) (ROTARY) (AME) TOOLS.  DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE		
Amount of surface pipe set and cemented 498 KB	_DV Tool Used?	
THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil, Gas)	Shut-in Gas, Dry, Disposal,	
Injection, Temporarily Abandoned, OWWO. Other	TONS PROMITICATED TO REGULATE THE OIL	
	.1AN 21 1983	
<u>A F F I D A V I T</u>	Condemantal Wishow Wighting France homely contified	

	AFFIDAVIT	Wightin Lines	Û/Ç
C. W. Sebits	,	being of lawful	age, hereby certifies
I am the Affiant, and The statements and allegati	I am familiar with the ons contained therein	contents of the	foregoing Affidavit.
SUBSCRIBED AND SWORN T	O BEFORE ME this20	C. W. Sebits	January ,

19<u>83</u>.

MY COMMISSION EXPLANATION November 24, 1985

Appt. Sires

Sue A. 1985

\*\* The person who can be reached by phone regarding any questions concerning this information.

Production -I.P.

Disposition of ges (vented, used on lease or sold)

Vented During Test

20.04

ACO-1 WELL HISTORY

31,287

5259'-5263'

CFPB

OPERATOR Pickrell Drilling Company LEASE# | Christian Churchec. 36 TWP.295 RGE. 25 WELL NO

FILL IN WELL INFORMATION AS REQUIRED: SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tests, cushion used, time tool open, flowing and shut-in pressures, and recoveries. FORMATION DESCRIPTION, CONTENTS, ETC. NAME DEPTH BOTTOM Check if no Drill Stem Tests Run. 5036'-5100' DST #1: Elog Tops: 30"-60"-60"-60" 4359 (-1777) Heebner rec 120' mud 4868 (-2286) Stark 4984 (-2402) 5126 (-2544) 5161 (-2579) 5238 (-2656) 5277 (-2698) 120' MCW B/KC IFP 59-98# B/Pawnee FFP 118-176#, ISIP 1597# Cherokee FSIP 1500# B/Inola Mississippi DST #2: 5254'-5274' 30"-60"-90"-120" GTS 13-15" 44 MCF 20" 65 MCF 30" 83 MCF 2nd op 10" 100 MCF 20" 125 MCF 30" 140 MCF RELEASED 40" 151 MCF 50" 158 MCF 8 1985 JAN 1 60" 163 MCF 70" 168 MCF FROM CONFIDENTIAL 80" 170 MCF 90" 173 MCF rec 60' drilling mud 70' GCM, IFP 59-127# FFP 49-88#, ISIP 1510# FSIP 1471# 5316'-5365', 30"-60"-30"-60"
weak blow, rec 120' drilling mud,
IFP 59-59#, FFP 59-59#, ISIP 137# 5384'-5310', 60"-60"-90"-120 strong blow, GTS 14" 2nd op DST #3: DST ##: 30" 3 MCF inc to 7 MCF and stab in 80", rec 90' HO&GCM 200' VHO & GCM, 40' gsy oil, IFP 49-88#, FFP 59-118# ISIP 1558#, FSIP 1627# FSIP 9B# If additional space is needed use Page 2, Report of all strings set - surface, intermediate, production, etc. CASING RECORD (New) or (Used) Sixe hole drilled Sixe coxing set Weight lbs/ft. Setting depth Type and percent edditives 12 1/4" 8 5/8" Surface 498'KB 275 3% gel, 2% CaCl Common Salt Sat. 7 7/8" 4 1/2" 5419 'KB Production 10.5# Common <u> 150</u> 5# Gilsonite/sx LINER RECORD PERFORATION RECORD Size & type Depth interval Top, ft. Sacks cement Shots per ft. 3/8" jet 5259'-5263' TUBING RECORD etting depti Size Packer set at 2 3/8" 52501 ACID, FRACTURE, SHOT, CEMENT SQUEEZE RECORD then telesters in both has to Acidize w/500 gal RA-8 L-53 acid. 5259'-5263' Foam frac w/5000# of 20-40 sand in 8000 gal 3% HCL, 0.6% HF 70 quality foam. 5259 -5263 ' Date of first production Producing method (flowing, pumping, ses (ift, etc.) Gravity Waiting on contract Veter Estimated %

627

Perforations