

RECEIVED

STATE OF KANSAS
STATE CORPORATION COMMISSION
130 S. Market, Room 2078
Wichita, Kansas 67202

OCT 15 2001

Well Plugging Record
K.A.R. -82-3-117

API NUMBER 15-047-21454-0000
LEASE NAME Schrader "A"
WELL NUMBER No. 1-27

KCC WICHITA
TYPE OR PRINT

NOTICE: Fill out completely and return
to Cons. Div. office within 30 days.

4620 Ft. from South Line of Section
3225 Ft. from East Line of Section

LEASE OPERATOR McCoy Petroleum Corporation SPOT LOCATION 75' East of Ne Nw
ADDRESS P. O. Box 780208 Section 27 Township 25s Range 20w
CITY, STATE, ZIP Wichita, Kansas 67278-0208 County Edwards
PHONE # 316-636-2737 Date Well Completed October 11, 2001
Character of Well Dry and Abandoned Date Plugging Commenced October 11, 2001
(Oil, Gas, D&A, SWD, Input, Water Supply Well) Date Plugging Completed October 11, 2001

The plugging proposal was approved on October 11, 2001 (date)
by Jim Holland (KCC District Agent's Name)

Is ACO-1 Filed? ? If not, is well log attached? Yes
Producing Formation(s) D&A Depth to Top Bottom T.D. 4849

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

FORMATION	CONTENT	FROM	TO	SIZE	PUT IN	PULL OUT
Surface Soil and Sands	Water sands	0	75	and		
Redbeds	Shale	75	350	8-5/8"	338.29	0'

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from _____ feet to _____ feet each set.

Plugged hole with 125sx 60/40 Poz, 6% Gel as follows: Heavy mud in hole.

1st plug @ 1300' with 50sx, 2nd plug @ 380' with 50sx, 3rd plug @ 40' with 10sx, cemented

to surface. Plug down at 7:30 am on 10/11/01 by Acid Services. Ticket # 04112.

Plugged rathole with 15sx (No mousehole).

Name of Plugging Contractor Sterling Drilling Company
Licence No. 5142
Address P.O. Box 1006 City: Pratt State: Kansas Zip 67124
NAME OF PARTY RESPONSIBLE FOR PLUGGING FEES: McCoy Petroleum Corporation (Operator)


STATE OF KANSAS COUNTY OF PRATT, ss.

Gary M. Talbott, Agent (Employee of Operator or (Operator) of above described well, being first
duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of
the above described well as filed that the same are true and correct, so help me God.

(Signature) Gary M. Talbott
(Gary M. Talbott, Vice- President of Sterling Drilling Company)

(Address) P.O. Box 1006 City: Pratt State: Kansas Zip 67124

SUBSCRIBED AND SWORN TO me this 15th day of October, 2001



Pamela S. Fields
(Notary Public)

My Commission Expires: _____

Form CP-4
Revised 12-92

R
OR

RECEIVED

OCT 15 2001

KCC WICHITA

Sterling Drilling Company, Rig #4

Box 1006, Pratt, Kansas 67124-1006
Office Phone (316) 672-9508, Fax 672-9509

SAMPLE LOG

Schrader "A" No. 1-27

LOCATION: 75' East of Ne Nw
API: 15-047-21454-0000

Section 27 T 25s R 20w
Edwards County, Kansas

OWNER: McCoy Petroleum Corporation
CONTRACTOR: Sterling Drilling Company, Rig #4

COMMENCED: 10/02/01
COMPLETED: 10/11/01

TOTAL DEPTH:	DRILLER	4849	FEET
	LOGGER	4846	FEET

Ground Elevation: 2247
KB Elevation: 2256

LOG

0 -	3 FEET	Top soil (No surface sands)
3 -	15 FEET	Clay
15 -	16 FEET	Sandstone
16 -	19 FEET	Shale
19 -	27 FEET	Sandstone
27 -	55 FEET	Shale
55 -	275 FEET	Sandstone
275 -	1285 FEET	Red beds and shale
1285 -	1295 FEET	Anhydrite
1295 -	2360 FEET	Shales and Salt
2360 -	4849 FEET	Limestone/Shales

CASING RECORDS

Spud @ 10:15 am on 10-02-01. Drilled 12-1/4" hole to 350'. Ran 8 joints of new 24# 8-5/8" surface casing tally 338.29' set at 349' KB. Cemented with 225 sacks 60/40 Poz, 2% Gel, 3% C.C. Cement did circulate. Plug down at 6:00 pm on 10-02-01 by Allied. Ticket # 08742.

PLUGGING REPORT

Plugged hole with 125sx 60/40 Poz, 6% Gel as follows: Heavy mud in hole.
1st plug @ 1300' with 50sx, 2nd plug @ 380' with 50sx, 3rd plug @ 40' with 10sx, cemented to surface. Plug down at 7:30 am on 10/11/01 by Acid Services. Ticket # 04112.
Plugged rathole with 15sx (No mousehole).

DEVIATION SURVEYS

1-1/2	degree(s) at	350	feet
1	degree(s) at	1038	feet
1	degree(s) at	4743	feet