

1 060414

API NUMBER 15- 101-21,088 - 0000

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

C SE NE, SEC. 28, T 17 S, R28 W/E  
3300 feet from S section line  
660 feet from E section line

TECHNICIAN'S PLUGGING REPORT  
Operator License # 9726

Lease Name Bryant Well # 1  
County Lane 147.88  
Well Total Depth 4550 feet  
Conductor Pipe: Size feet  
Surface Casing: Size 8 5/8 feet 388

Operator: Gruss Petroleum Management, Inc.  
Name & Address 900 Building of the Southwest  
Midland, TX 79701

Abandoned Oil Well Gas Well Input Well SMD Well D&A X

Other well as hereinafter indicated

Plugging Contractor DNB Drilling, Inc. License Number 5476

Address 535 North Oliver, Wichita, KS 67208

Company to plug at: Hour: 7:00 am Day: 30 Month: November Year: 19 84

Plugging proposal received from John Taylor

(company name) DNB (phone) 316-687-5471

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 2070' with 50 sx cement

2nd plug at 1230' with 50 sx cement

3rd plug at 400' with 50 sx cement

4th plug solid bridge hulls - plug at 40' -- cement to surface with 10 sx cement

6th plug to circulate rat hole with 15 sx cement  
Plugging Proposal Received by Paul A. Luthi  
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 8:30 am Day: 30 Month: November Year: 19 84

ACTUAL PLUGGING REPORT 1st plug at 2070' with 50 sx cement, 2nd plug at 1230' with 50 sx cement, 3rd plug at 400' with 50 sx cement, 4th & 5th plugs - solid bridge - hulls - plug at 40' -- cement to surface with 10 sx cement, 6th plug to circulate rat hole with 15 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION  
12-5-84  
DEC 05 1984

Remarks: Used 60/40 Pozmix 2% gel 3%cc by Halliburton  
(If additional description is necessary, use BACK of this form.)

(878 / did not) observe this plugging.  
INVOICED

Signed Paul A. Luthi SP  
(TECHNICIAN)

DATE 12-12-84  
INV NO. 5953