

KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

(See Instructions on Reverse Side)

Type Test:

- Open Flow
- Deliverability

Test Date:

API No. 15

175-~~20176~~ 20,176-0000

Company Kaiser Francis Oil Company		Lease McDonald		Well Number 1-18	
County Seward	Location C SE	Section 18	TWP 35S	RNG (E/W) 33W	Acres Attributed
Field Liberal SE		Reservoir Chester		Gas Gathering Connection DLP	
Completion Date 6/26/72		Plug Back Total Depth 6409		Packer Set at None	
Casing Size 4.5	Weight 10.5	Internal Diameter 4.052	Set at 6445	Perforations 6320	To 6340
Tubing Size 2.375	Weight 4.7	Internal Diameter 1.995	Set at 6295	Perforations	To
Type Completion (Describe) Single		Type Fluid Production		Pump Unit or Traveling Plunger? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Producing Thru (Annulus / Tubing) Tubing		% Carbon Dioxide		% Nitrogen	
Vertical Depth(H) 6330		Pressure Taps Pipe		(Meter Run) (Prover) Size 4	
Pressure Buildup: Shut in 2/12/12 19__ at __ (AM) (PM) Taken 2/13/12 19__ at __ (AM) (PM)		Well on Line: Started 19__ at __ (AM) (PM) Taken 19__ at __ (AM) (PM)			

OBSERVED SURFACE DATA

Static/ Dynamic Property	Orifice Size inches	Circle one: Meter or Prover Pressure psig	Pressure Differential in (h) Inches H ₂ O	Flowing Temperature t	Well Head Temperature t	Casing Wellhead Pressure (P _w) or (P _i) or (P _e)		Tubing Wellhead Pressure (P _w) or (P _i) or (P _e)		Duration (Hours)	Liquid Produced (Barrels)
						psig	psia	psig	psia		
Shut-in								230		24	
Flow											

FLOW STREAM ATTRIBUTES

Plate Coefficient (F ₁) (F ₂) Mcf/d	Circle one: Meter or Prover Pressure psia	Press Extension $\sqrt{P_w \times H_w}$	Gravity Factor F _g	Flowing Temperature Factor F _t	Deviation Factor F _{dv}	Metered Flow R (Mcf/d)	GOR (Cubic Feet/ Barrel)	Flowing Fluid Gravity G _w

(OPEN FLOW) (DELIVERABILITY) CALCULATIONS

$(P_c)^2 =$ _____ : $(P_w)^2 =$ _____ : $P_w =$ _____ % $(P_c - 14.4) + 14.4 =$ _____ : $(P_w)^2 = 0.207$
 $(P_c)^2 =$ _____

$(P_c)^2 - (P_w)^2$ or $(P_c)^2 - (P_w)^2$	$(P_c)^2 - (P_w)^2$	Choose formula 1 or 2: 1. $P_c^2 - P_w^2$ 2. $P_c^2 - P_w^2$ divided by: $P_c^2 - P_w^2$	LOG of formula 1. or 2. and divide by: $P_c^2 - P_w^2$	Backpressure Curve Slope = "n" ----- Assigned Standard Slope	n x LOG []	Antilog	Open Flow Deliverability Equals R x Antilog Mcf/d

Open Flow Mcfd @ 14.85 psia Deliverability Mcfd @ 14.65 psia

The undersigned authority, on behalf of the Company, states that he is duly authorized to make the above report and that he has knowledge of the facts stated therein, and that said report is true and correct. Executed this the 28 day of February, 192013

Witness (if any)

For Commission

Robert Major
For Company

RECEIVED
MAR 04 2013

Checked by _____
KCC WICHITA

I declare under penalty or perjury under the laws of the state of Kansas that I am authorized to request exempt status under Rule K.A.R. 82-3-304 on behalf of the operator Kaiser Francis Oil Company and that the foregoing information and statements contained on this application form are true and correct to the best of my knowledge and belief based upon gas production records and records of equipment installation and/or of type completion or upon use of the gas well herein named.

I hereby request a permanent exemption from open flow testing for the McDonald 1-18 gas well on the grounds that said well:

(Check one)

- is a coalbed methane producer
- is cycled on plunger lift due to water
- is a source of natural gas for injection into an oil reservoir undergoing ER
- is on vacuum at the present time; KCC approval Docket No. _____
- is incapable of producing at a daily rate in excess of 150 mcf/D

Date: 2/28/13

Signature: Robert Mays

Title: Production Records Manager

Instructions: All active gas wells must have at least an original G-2 form on file with the conservation division. If a gas well meets the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to obtain a testing exemption.

At some point during the succeeding calendar year, wellhead shut-in pressure shall be measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under "observed surface data." Shut-in pressure shall thereafter be reported yearly in the same manner.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than thirty (30) days after the taking of the pressure reading. The form must be signed and dated on the front side as though it was a verified report of test results.