

KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

Type Test:

(See Instructions on Reverse Side)

Open Flow
Deliverability

Test Date:
01/11/2013 - 01/12/2013

API No. 15
15-047-21,131 - 0000

Company F.G. Holl Company, L.L.C.		Lease BRITTON		Well Number 3-15	
County Edwards	Location SW NW SW	Section 15	TWP 24S	RNG (E/W) 17W	Acres Attributed
Field Wayne		Reservoir Mississippi-Kinderhook	Gas Gathering Connection Semgas Gathering L.L.C.		
Completion Date 11/17/1983		Plug Back Total Depth		Packer Set at None	
Casing Size 4-1/2"	Weight 10.5#	Internal Diameter	Set at 4492'	Perforations 4386'- 4390'	To 4328'-4342'
Tubing Size 2"	Weight 4.7#	Internal Diameter	Set at 4316'	Perforations	To
Type Completion (Describe) Commingled		Type Fluid Production		Pump Unit or Traveling Plunger? Yes / No Pump unit	
Producing Thru (Annulus / Tubing) Tubing		% Carbon Dioxide		% Nitrogen	Gas Gravity - G _s
Vertical Depth(H)		Pressure Taps Flange		(Meter Run) (Prover) Size 2"	
Pressure Buildup: Shut in 01/11/2013 19 at 8:00 (AM) (PM) Taken 01/11/2013 19 at 8:00 (AM) (PM)					
Well on Line: Started 01/12/2013 19 at 8:00 (AM) (PM) Taken 01/12/2013 19 at 8:00 (AM) (PM)					

RECEIVED
JAN 24 2013
KCG WICHITA

OBSERVED SURFACE DATA

Duration of Shut-In 24 Hours

Static / Dynamic Property	Orifice Size Inches	Circle one: Meter or Prover Pressure psig	Pressure Differential in (h) Inches H ₂ O	Flowing Temperature t	Well Head Temperature t	Casing Wellhead Pressure (P _w) or (P _i) or (P _c)		Tubing Wellhead Pressure (P _w) or (P _i) or (P _c)		Duration (Hours)	Liquid Produced (Barrels)
						psig	psia	psig	psia		
Shut-In						49		20		24	
Flow											

FLOW STREAM ATTRIBUTES

Plate Coefficient (F _p) (F _p) Mcfd	Circle one: Meter or Prover Pressure psia	Press Extension $\frac{1}{2} P_m \times H_w$	Gravity Factor F _g	Flowing Temperature Factor F _{tt}	Deviation Factor F _{pv}	Metered Flow R (Mcf/d)	GOR (Cubic Feet/ Barrel)	Flowing Fluid Gravity G _m

(OPEN FLOW) (DELIVERABILITY) CALCULATIONS

(P_c)² = _____ : (P_w)² = _____ : P_d = _____ % (P_c - 14.4) + 14.4 = _____ : (P_e)² = 0.207 : (P_d)² = _____

(P _c) ² - (P _e) ² or (P _c) ² - (P _d) ²	(P _c) ² - (P _w) ²	Choose formula 1 or 2: 1. P _c ² - P _e ² 2. P _c ² - P _d ² divided by: P _c ² - P _w ²	LOG of formula 1. or 2. and divide by: $\frac{P_c^2 - P_e^2}{P_c^2 - P_w^2}$	Backpressure Curve Slope = "n" ----- Assigned Standard Slope	n x LOG	Antilog	Open Flow Deliverability Equals R x Antilog Mcfd

Open Flow Mcfd @ 14.65 psia Deliverability Mcfd @ 14.65 psia

The undersigned authority, on behalf of the Company, states that he is duly authorized to make the above report and that he has knowledge of the facts stated therein, and that said report is true and correct. Executed this the 23rd day of January, 2013.

Witness (if any)

For Company
Lovness D. Payne

For Commission

Checked by

RECEIVED

Form G-2
(Rev. 1/03)

JAN 24 2013

KCC WICHITA

I declare under penalty or perjury under the laws of the state of Kansas that I am authorized to request exempt status under Rule K.A.R. 82-3-304 on behalf of the operator F.G. Holl Company, L.L.C. and that the foregoing information and statements contained on this application form are true and correct to the best of my knowledge and belief based upon gas production records and records of equipment installation and/or of type completion or upon use of the gas well herein named.

I hereby request a permanent exemption from open flow testing for the BRITTON 3-15 gas well on the grounds that said well:

(Check one)

- is a coalbed methane producer
- is cycled on plunger lift due to water
- is a source of natural gas for injection into an oil reservoir undergoing ER
- is on vacuum at the present time; KCC approval Docket No. _____
- is incapable of producing at a daily rate in excess of 250 mcf/D

Date: 01/21/2013

Signature: *Loueness*

Title: Petroleum Geologist

Instructions: All active gas wells must have at least an original G-2 form on file with the conservation division. If a gas well meets the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to obtain a testing exemption.

At some point during the succeeding calendar year, wellhead shut-in pressure shall be measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under "observed surface data." Shut-in pressure shall thereafter be reported yearly in the same manner.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than thirty (30) days after the taking of the pressure reading. The form must be signed and dated on the front side as though it was a verified report of test results.