STATE CORPORATION COMMISSION CONSERVATION DIVISION - Plugging Section 130 S. Market, Room 2078 Wichita, Kansas 67202 6-18

PERATOR LICENSE # 5038 PERATOR ROBINSON OIL COMPANY	SECTION 8 TOWNS	
		HIP 31 RANGE 5W
	1650'I	FEET FROM S SECTION LINE
ROBINSON OIL COMPANI		EET FROM E SECTION LINE
AME & 300 WEST DOUGLAS #420		
DDRESS WICHITA, KS 67202	LEASE NAME:S	CHROCK "C" #1  HARPER  4578'   B 3580
	COUNTY:	HARPER
	WELL TOTAL DEPTH:	: <u>4578'   B 3380</u>
	PIPE:	<u>4</u> 1/2" @ 3719'
	SURFACE CASING:	8 5/8" @ 263'
ANDONED OIL WELL X GAS WELL	_ INPUT WELL	SWD D&A
THER WELL AS HEREINAFTER INDICATED:		
THER WEDL AS REALINAFIER INDICATED;		
LUGGING CONTRACTOR: MIKE'S TESTING &	SALVAGE	
DDRESS: P.O. BOX 209, CHASE, KS 679		
MIKE'S TESTING & SALVA  SAND TO 3460' AND 4 SA  35 SACKS AT 900'  35 SACKS AT 525'  310' TO 0	CKS	
LUGGING PROPOSAL RECEIVED BY: M.W.		
OMPLETED: HOUR: 12:30 DAY: 18	MONTH: 6 YEAR	t: <u>1996</u>
OMPLETED: HOUR: 12:30 DAY: 18		
	3460' AND 4 SACKS OF	F COMMOM. SHOT 4 1/2"
OMPLETED: HOUR: 12:30 DAY: 18  CTUAL PLUGGING REPORT: SANDED BOTTOM TO	3460' AND 4 SACKS OF PUMPED 35 SACKS. PU	F COMMOM. SHOT 4 1/2" ULLED TO 525'. PUMPED
OMPLETED: HOUR: 12:30 DAY: 18  CTUAL PLUGGING REPORT: SANDED BOTTOM TO ASING OFF AT 2891'. PULLED TO 900'.	3460' AND 4 SACKS OF PUMPED 35 SACKS. PU	F COMMOM. SHOT 4 1/2" ULLED TO 525'. PUMPED
OMPLETED: HOUR: 12:30 DAY: 18  CTUAL PLUGGING REPORT: SANDED BOTTOM TO ASING OFF AT 2891'. PULLED TO 900'.	3460' AND 4 SACKS OF PUMPED 35 SACKS. PU	F COMMOM. SHOT 4 1/2" ULLED TO 525'. PUMPED
OMPLETED: HOUR: 12:30 DAY: 18  CTUAL PLUGGING REPORT: SANDED BOTTOM TO ASING OFF AT 2891'. PULLED TO 900'.	3460' AND 4 SACKS OF PUMPED 35 SACKS. PU	F COMMOM. SHOT 4 1/2" ULLED TO 525'. PUMPED
OMPLETED: HOUR: 12:30 DAY: 18  CTUAL PLUGGING REPORT: SANDED BOTTOM TO ASING OFF AT 2891'. PULLED TO 900'.	3460' AND 4 SACKS OF PUMPED 35 SACKS. PU	F COMMOM. SHOT 4 1/2" ULLED TO 525'. PUMPED
OMPLETED: HOUR: 12:30 DAY: 18  CTUAL PLUGGING REPORT: SANDED BOTTOM TO ASING OFF AT 2891'. PULLED TO 900'.	3460' AND 4 SACKS OF PUMPED 35 SACKS. PU D CEMENT TO SURFACE.	F COMMOM. SHOT 4 1/2" ULLED TO 525'. PUMPED


I DID - OBSERVE THIS PLUGGING.

JACK LUTHI

WV. NO.

FORM CP-2/3 **REV. 3/90**  FÖRM 925322 REV. (8-80)

<b>Dresser Atlas</b>	



## Compensated Densilog® Compensated Neutron Gamma Ray



BAESSEA)	Gal	mma K	ay	
FILE NO.				
API NO 072	COMPANY_	ROBINSON C	OIL COMPANY	
15-007-20803	WELL	SCHROCK "C	NO. 1	
	FIELD	WILDCAT	· <u> </u>	,
	COUNTY	HARPER	STATE_	KANSAS
	LOCATION:			Other Services
	150'	NE of C-NE	I-SE	DIFL
	SEC8		_RGE_5W	
Permanent Datum_GROU Log Measured from_KEL Drilling Measured from KE	LY BUSHING	ElevElev	1314 e Permanent Datum	Elev. KB 1324 DF 1321 GL 1314
Date	5-30-82			
Run No.	ONE		CO:	
Service Order	27399		MOT CO.	<u> </u>
Depth-Driller	4577	-08INS	15 F DO 5	
Depth-Logger	4578	K Talk Lik		
Bottom Logged Interval	4577	44		
Top Logged Interval	1000			
Casing-Driller	8-5/8@263	@	@	@
Casing-Logger	263			
Bit Size	7-7/8"			
Type Fluid in Hole	STARCH			
Density and Viscosity	7.1 51			
pH and Fluid Loss	10.0 10.4cc	СС	. 00	cc
Source of Sample	FLOWLINE			
Rm @ Meas. Temp.	.93 @84 °F	@ °F	@ °F	. @ °F
Rmf @ Meas. Temp.	.69 @84 °F	@ °F	@ <sup>(</sup> °F	@ ° ғ
Rmc @ Meas. Temp.	1.16@84 °F	@ °F	@ °F	@ °F
Source of Rmf and Rmc	MEAS			
Rm @ BHT	.66 @120°F	@ °F	@ °F	@ °F
Time Since Circ.	6 HRS.			1
Max. Rec. Temp. Deg. F.	12() °F	۰F	۰F	°F
Equip. No. and Location	6138 GB			
Recorded By	RHODES-SCHU	LZE		
Witnessed By		D. ROBINSO:	7	