KANSAS

STATE CORPORATION COMMISSION

CONSERVATION DIVISION AGENT'S REPORT

J. Lewis Brock
Administrator
245 North Weter
Wichita, KS 67202

API Number 15 -077 - 20,620-000 (of this well)

chandoned 0il Well Gas Well Input Well SWD Well D&AX Cher well as hereafter indicated Clugging Contractor Dunbar Drilling Co., Inc. Conductor State Completed: Hour 2: 45 Am. Day 28 Month 9 Year 1980 Che above well was plugged as follows: 262' 8 5/8" casing. Set 40 sax cement plug at 270'-Bridge at 40' of 10 sax cement to 5' below Gl. 10 sax in rat hole. Cemented by Howell Conservation Commission Conservation Division Wichia, Kansaya	casa Mana Cmith	Well No. 3
Total Depth 4368 Abandoned Oil Well Gas Well Input Well SWD Well D&AX Other well as hereafter indicated Plugging Contractor Dunber Drilling Co., Inc. Address 5252 N.Broadway, Wichita, Ks. 67219 License No. Operation Completed: Hour 2:45 Am. Day 28 Month 9 Year 1980 The above well was plugged as follows: 262' 8 5/8" casing. Set 40 sax cement plug at 270'-Bridge at 40' of 10 sax cement to 5' below Gl. 10 sax in rat hole. Cemented by Howell Conservation Division OCT - 2 1980 CONSERVATION DIVISION WIChita, Kansaa		
Abandoned Oil Well Gas Well Input Well SWD Well D&AX Other well as hereafter indicated Plugging Contractor Dunber Drilling Co., Inc. Address 5252 N.Broadway, Wichita, Ks. 67219 License No. Operation Completed: Hour 2: 45 Am. Day 28 Month 9 Year 1980 The above well was plugged as follows: 262' 8 5/8" casing. Set 40 sax cement plug at 270'-Bridge at 40' of the sax cement to 5' below Gl. 10 sax in rat hole. Cemented by Howell Conservation Commission OCT - 2 1980 CONSERVATION DIVISION WICHIA, Kansaya		
Plugging Contractor Dunber Drilling Co., Inc. Address 5252 N.Broadway, Wichita, Ks. 67219 License No. Departion Completed: Hour 2:45 Am. Day 28 Month 9 Year 1980 The above well was plugged as follows: 262' 8 5/8" casing. Set 40 sax cement plug at 270'-Bridge at 40' of 10 sax cement to 5' below Gl. 10 sax in rat hole. Cemented by Howell Components of the components of th	County <u>Harper</u>	Total Depth 4368
Plugging Contractor Dunber Drilling Co., Inc. Address 5252 N. Broadway, Wichita, Ks. 67219 License No. Deparation Completed: Hour 2: 45 Am. Day 28 Month 9 Year 1980 The above well was plugged as follows: 262' 8 5/8" casing. Set 40 sax cement plug at 270'-Bridge at 40' of 10 sax cement to 5' below Gl. 10 sax in rat hole. Cemented by Howell Conservation Division Wichita, Kansaa	bandoned Oil Well Gas Well	Input WellD & A X
Address 5252 N.Broadway, Wichita, Ks. 67219 Departion Completed: Hour 2:45 Am. Day 28 Month 9 Year 1980 The above well was plugged as follows: 262' 8 5/8" casing. Set 40 sax cement plug at 270'-Bridge at 40' of 10 sax cement to 5' below Gl. 10 sax in rat hole. Cemented by Howell Components of the component o	other well as hereafter indicated	
Operation Completed: Hour 2:45 Am. Day 28 Month 9 Year 1980 The above well was plugged as follows: 262' 8 5/8" casing. Set 40 sax cement plug at 270'-Bridge at 40' of 10 sax cement to 5' below Gl. 10 sax in rat hole. Cemented by Howell STATE CORPORATION COMMISSING CONSERVATION DIVISION Wichita, Kansaa	Plugging Contractor Dunbar Drilli	ng Co., Inc.
Operation Completed: Hour 2:45 Am. Day 28 Month 9 Year 1980 The above well was plugged as follows: 262' 8 5/8" casing. Set 40 sax cement plug at 270'-Bridge at 40' of 10 sax cement to 5' below Gl. 10 sax in rat hole. Cemented by Howell STATE CORPORATION COMMISSING CONSERVATION DIVISION Wichita, Kansaa	Address 5252 N.Broadway, Wichit	ta, Ks. 67219 License No.
The above well was plugged as follows: 262' 8 5/8" casing. Set 40 sax cement plug at 270'-Bridge at 40' of the sax cement to 5' below Gl. 10 sax in rat hole. Cemented by Howell STATE CORPORATION COMMISSING TO THE CONSERVATION DIVISION WICHIA, Kansaya	•	·
262' 8 5/8" casing. Set 40 sax cement plug at 270'-Bridge at 40' of 10 sax cement to 5' below Gl. 10 sax in rat hole. Cemented by Howe STATE CORPORATION COMMISSING CONSERVATION DIVISION WICHITA, Kansaya	•	
OCT - 2 1980 IO - 2 - 80 CONSERVATION DIVISION WICHITA, Kansay	The above well was plugged as follow	WS:
RECEIVED STATE CORPORATION COMMISSIN OCT - 2 1980 CONSERVATION DIVISION WICHITA, KANSAN	262' 8 5/8" casing. Set 40 s	ax cement plug at 270'-Bridge at 40' &
RECEIVED STATE CORPORATION COMMISSIN OCT - 2 1980 CONSERVATION DIVISION WICHITA, KANSAN	10 sax cement to 5' below Gl	. 10 sax in rat hole. Cemented by Howco
OCT - 2 1980 10 - 2 - 80 CONSERVATION DIVISION Wichita, Kansay		
OCT - 2 1980 10 - 2 - 80 CONSERVATION DIVISION WICHITA, KANSAS		
OCT - 2 1980 CONSERVATION DIVISION Wichita, Kansay		
OCT - 2 1980 10 - 2 - 80 CONSERVATION DIVISION WICHITA, KANSAS		RECEIVED
OCT - 2 1980 10 - 2 - 80 CONSERVATION DIVISION WICHITA, KANSAS		STATE CORPORATION COMMISSION
CONSERVATION DIVISION WICHITA, Kansay		
, wichita, Kansas		:00T 0 €000
/ /7		17-2-90
I DOVERN CONTITUITOS TOS BROUG MALL WAS WINGOOD AS BANKIN SEATAL //		CONSERVATION DIVISION
Signed: Signed:	I hereby certify that the above well	CONSERVATION DIVISION Wichita, Kansas 1 was plugged as berein stated.

INVOICED

NV. NO. 3263-W