

7-30

359  
R

To: 1 031166  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 165-21,584 -0000  
NE SE NE, SEC. 31, T 18 S, R 17 W/E  
3630 feet from S section line  
330 feet from E section line

TECHNICIAN'S PLUGGING REPORT  
Operator License # 5393  
Operator: A.L. Abercrombie, Inc.  
Name & Address: 150 N. Main, Suite 801  
Wichita, KS 67202

Lease Name Tammen Well # 1  
County Rush 126.16  
Well Total Depth 3882 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 1213

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X  
Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Abercrombie RTD, Inc. License Number 30684  
Address 801 Union Center, Wichita, KS 67202

Company to plug at: Hour: 6 p.m. Day: 30 Month: 7 Year: 19 91

Plugging proposal received from Tony Martin  
(company name) Abercrombie RTD, Inc. (phone) 316-262-1841

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1195-1227'

- 1st plug at 1230' with 50 sx cement,
- 2nd plug at 600' with 30 sx cement,
- 3rd plug at 40-0' with 10 sx cement,
- 4th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Steve Durrant (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 8:45 p.m. Day: 30 Month: 7 Year: 19 91

ACTUAL PLUGGING REPORT 1st plug at 1230' with 50 sx cement,

- 2nd plug at 600' with 30 sx cement,
- 3rd plug at 40-0' with 10 sx cement,
- 4th plug to circulate rathole with 15 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION  
8-7-91  
AUG 07 1991

Remarks: Used 60/40 Pozmix 6% gel by Allied.  
(If additional description is necessary, use BACK of this form.)

INVOICED  
DATE 8-16-91  
INV. NO. 32746

Signed Steve Durrant (TECHNICIAN)

EFFECTIVE DATE 2-24-91

FORM MUST BE TYPED  
FORM C-1 4/90

State of Kansas 165-21,584 - ~~0000~~

NOTICE OF INTENTION TO DRILL

Must be approved by the K.C.C. five (5) days prior to commencing well

FORM MUST BE SIGNED  
ALL BLANKS MUST BE FILLED

Expected Spud Date 7 22 91  
month day year

NE SE NE Sec 31 Twp 18 S, Rg 17 East West

OPERATOR: License # 5393  
Name: A. L. Abercrombia, Inc.  
Address: 150 N. Main, Suite 801  
City/State/Zip: Wichita, KS, 67202  
Contact Person: Jack L. Partridge  
Phone: 316-262-1841

3630' FSL  
330' FEL  
feet from South line of Section  
feet from East line of Section  
(Note: Locate well on Section Plat on Reverse Side)

CONTRACTOR: License #: 30684  
Name: Abercrombia RTD, Inc.

County: Rush  
Lease Name: Tammen Well #: 1  
Field Name: unknown

Well Drilled For: Well Class: Type Equipment:  
 Oil ... Inj ... Infield  Mud Rotary  
 Gas ... Storage ... Pool Ext.  Air Rotary  
 CWMD ... Disposal ... Wildcat  Cable  
 Seismic; ... # of Holes

Is this a Prorated Field? ... yes  no  
Target Formation(s): Arbuckle  
Nearest lease or unit boundary: 330'  
Ground Surface Elevation: unknown feet MSL

If CWMD: old well information as follows:  
Operator: N/A  
Well Name: \_\_\_\_\_  
Comp. Date: \_\_\_\_\_ Old Total Depth \_\_\_\_\_

Domestic well within 330 feet: ... yes  no  
Municipal well within one mile: ... yes  no  
Depth to bottom of fresh water: 200'  
Depth to bottom of usable water: 500' 480'

Directional, Deviated or Horizontal wellbore? ... yes  no  
If yes, total depth location: N/A

Surface Pipe by Alternate: ... 1  2  
Length of Surface Pipe Planned to be set: 1200'  
Length of Conductor pipe required: None  
Projected Total Depth: 3800'  
Formation at Total Depth: Arbuckle

262 6894

Exp. 1/19/92

AFFIDAVIT

Water Source for Drilling Operations:  
 well  farm pond  other  
DWR Permit #: will file  
Will Cores Be Taken?: ... yes  no  
If yes, proposed zone: N/A 200' Alt: II Reg.

\* Alt 2 completion

Pusher Jerry SPUD DATE 7-23-91 INIT. RLW

LENGTH SURFACE PLANNED 1200'

RESERVE PIT STATUS- REMOVE FLUID LINED  
after salt sect. bbls. when done bbls.

RATHOLED AHEAD? Y N SIZE HOLE  
SURFACE PIPE 8 7/8 @ 12 1/3 CONDUCTOR  
ANHYDRITE T-1195 B-1227 ELEVATION  
3812

TD 3310 FORMATION Arbuckle

RAN PIPE @	DV TOOL	ALT II DONE
	SX	Y N
<input checked="" type="checkbox"/> Arbuckle Plug @ <u>Arbuckle</u> Ft. W/ <u>40</u> SX		
<u>2nd</u> Hug./Council @ <u>1230</u> Ft. W/ <u>50</u> SX		
<u>3rd</u> Anhydrite Base @ <u>600</u> Ft. W/ <u>30</u> SX		
<u>1/2</u> Base Anyh. @ _____ Ft. W/ _____ SX		
<u>1/2</u> Plug @ _____ Ft. W/ _____ SX		
<u>Bottom</u> Surface @ _____ Ft. W/ _____ SX		
<u>4/1991</u> Plug @ <u>40-0</u> Ft. W/ <u>10</u> SX		

RAT HOLES CIRC/W 5 SX MOUSE HOLE W/ 1A SX

WATER WELL \_\_\_\_\_ SX (Irr. Well Pond Hauling X)

TECHNICIAN SD DATE 7/28/91

TYPE OF CEMENT 60/40 6% gel.

STARTING TIME 6:00 (AM/PM) DATE 7-30-91

COMPLETION TIME 8:45 (AM/PM) DATE 7-30-91

CEMENT COMPANY Allied DG

STATE CORPORATION COMMISSION

AUG 7 1991

Wichita, Kansas

FROM

07/19/91 14:81 P. 2 TOTAL P. 2