

1030336

To:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-165-21,273-00-00NW SE SE, SEC. 2, T 17 S, R 18 W EX990 feet from S section line990 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5140Lease Name Appl "B" Well # 1Operator: Frontier Oil CompanyCounty Rush 130.90

Name &

Address 1720 Kansas State Bank BuildingWell Total Depth 3720 feetWichita, KS 67202Conductor Pipe: Size feetSurface Casing: Size 8 5/8 feet 382Abandoned Oil Well Gas Well Input Well SWD Well D&A XOther well as hereinafter indicated Plugging Contractor Red Tiger Drilling Co. License Number 5302Address 1720 Kansas State Bank Building, Wichita, KS 67202Company to plug at: Hour: 10:00 am Day: 24 Month: November Year: 19 84Plugging proposal received from Mike Rempe(company name) Red Tiger (phone) 316-263-2371were: to fill hole with heavy mud and spot cement through drill pipe1st plug at 1260' with 50 sx cement2nd plug at 840' with 50 sx cement3rd plug at 420' with 40 sx cementsolid bridge4th plug hulls - plug at 40' -- cement to surface with 10 sx cement6th plug to circulate rat hole with 10 sx cementPlugging Proposal Received by Steve Hurnant
(TECHNICIAN)Plugging Operations attended by Agent?: All Part None XOperations Completed: Hour: 12:00 pm Day: 24 Month: November Year: 19 84ACTUAL PLUGGING REPORT 1st plug at 1260' with 50 sx cement. 2nd plug at 840' with 50sx cement, 3rd plug at 420' with 40 sx cement, 4th & 5th plugs - solid bridge - hulls -plug at 40' -- cement to surface with 10 sx cement, 6th plug to circulate rat hole with10 sx cement.RECEIVED
STATE CORPORATION COMMISSION

NOV 28 1984

11-28-1984

CONSERVATION DIVISION
Wichita, KansasRemarks: Used 60/40 Pozmix 2% gel 3% cc by Allied.(If additional description is necessary, use BACK of this form.)

(did / did not) observe this plugging.

Signed Steve Hurnant
(TECHNICIAN)DATE 12-3-84INV. NO. 5739

11-24