3	3	6
---	---	---

U/U/40	AP1 NUMBER 15- 165-21,379-00-00
TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING	SE NW SE. SEC. 21 . T 17 S, R 20 W/R
WICHITA, KANSAS 67202	1650 feet from S section line
TECHNICIAN'S PLUGGING REPORT	feet from E section line
Operator License # 9067	Lease Name Rixon Well # 1 A
Operator: DaMar Resources	County Rush /34.62
Name& P.O. Box 70	Well Total Depth 4142 feet
Hays, KS 67601	Conductor Pipe: Sizefeet
	Surface Casing: Size 8 5/8 feet 515
Abandoned Oil Well X Gas Well	Input Well SWD Well D&A
Other well as hereinafter indicated	
Plugging Contractor DaMar Resources	License Number 9067
Address P.O. Box 70, Hays, KS 67601	
	31 Month: 10 Year:19 89
Plugging proposal received from Curtis	
	(phone) <u>913-625-0020</u>
were: 5½" at 4141' PBTD 4118' Perfs at	4042-46' Port Collar at 1420', cemented w/300 sx 50/50 Poz. 6% gel, cement circulate
	sx 50/50 roz. 6% ger, cement criculate
1st plug pump down 5½" with 3 sx hulls, ge	el to 100' below Anhydrite, to surface with cement
2nd plug pump 100 sx cement down annulus i	if it will take.
	AECEIVED JATE CORPORATION COMM
Plugging Prope	osal Received by Steve Pfeife NOV - 6 1930
, vagging viopo	(TECHNICIAN)
Plugging Operations attended by Agent?: A	CONSCRIVATION DIVISION
Operations Completed: Hour: 2 p.m. Day:	31 Month: 10 Year:1989
ACTUAL PLUGGING REPORT 1st plug pumped 300	1bs. hulls, 32 sx ATL cement and pressured
to 2000#, bled pressure back to 500#, shut	in down $5\frac{1}{2}$ ", pressured 8 $5/8$ " to 500 #,
would not take.	
Remarks: Used ATL cement by Allied. No	
VOICE Dif additional description is	necessary, use BACK of this form.)
i (did) वेनक क्रिक्र) observe this plugging.	0 4 1