

1080114

To:  
 STATE CORPORATION COMMISSION  
 CONSERVATION DIVISION - PLUGGING SECTION  
 200 COLORADO DERBY BUILDING  
 WICHITA, KANSAS 67202

## TECHNICIAN'S PLUGGING REPORT

Operator License # 5011

Operator: Viking Resources  
 Name & 217 East William  
 Address Wichita, KS 67202-4005

API NUMBER 15-165-21,177-0000SE NW NW, Sec. 9, T 17 S, R 19 W990 feet from N/S section line990 feet from W/E section lineLease Name Curtis Well # 1County RushWell Total Depth 3913 feet 127.18Conductor Pipe: Size    feet   Surface Casing: Size 8 5/8 feet 261Abandoned Oil Well    Gas Well    Input Well    SWD Well    D&A XOther well as hereinafter indicated   Plugging Contractor Mallard Drilling License Number 5651Address Century Plaza Building, Suite 405, Wichita, KS 67202Company to plug at: Hour: 7:00 am Day: 6 Month: March Year: 1984VERBAL PLUGGING ORDERS GIVEN TO Cozby(company name) Mallard (phone) 316-263-8218were: to fill hole with heavy mud and spot cement through drill pipe1st plug at 1325' with 50 sx cement2nd plug at 700' with 50 sx cement3rd plug at 300' with 40 sx cementsolid bridge4th plug hulls - plug at 40' -- cement to surface with 10 sx cement6th plug to circulate rathole with 10 sx cement, 7th plug to circulate mousehole with 10 sx cementSigned J. H. M  
(TECHNICIAN)Plugging Operations attended by Agent?: All    Part    None XOperations Completed: Hour: 9:00 am Day: 6 Month: March Year: 19 84ACTUAL PLUGGING REPORT 1st plug at 1325' with 50 sx cement, 2nd plug at 700' with50 sx cement, 3rd plug at 300' with 40 sx cement, 4th & 5th plugs + solid bridge -hulls - plug at 40' -- cement to surface with 10 sx cement, 6th & 7th plugs tocirculate rathole and mousehole with 10 sx cement eachRemarks: Use 60/40 Pozmix 2% gel 3% cc by Allied

I hereby certify that the above plugging instructions were given as herein stated  
 and that I (did not) observe SECO W/ plugging.  
 STATE CORPORATION COMMISSION

MAR 1 1984

Signed

J. H. M  
(TECHNICIAN)CONSERVATION DIVISION  
WICHITA, KANSASFORM CP-2/3  
Rev. 9-82

INVOICED

DATE 3-22-84INV. NO. 0896 3-6