To:	1 0/1143 3- 3 - 39	API NUMBER 15- 165-20,752			
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 10 ¹ 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202		E SE SE NE, SEC. 3	T 18	_s, R18_w	/发
		2970	feet from	S section 11	ne
TECHNICIA	N'S PLUGGING REPORT	320	feet from	E section []	n e
Operator	License / 5886	Lease Name Weigand		1	
	Chief Drilling, Inc.	County Rush			
Name& Address	120 S. Market, Ste. 300	Well Total Depth_	3842	124.86	et
	Wichita, KS 67202	Conductor Pipe: S	120	feet	
		Surface Casing: S	1208 5/8 f	eet 1212	
Abandoned	Oli Weli X Gas Well				
	t as hereinafter indicated				
Plugging	Contractor Chief Drilling, Inc.	L	icense Numbe	5886	
	120 S. Market, Ste. 300, Wichita, KS 6				
	o plug at: Hour: 10 a.m. Day:		3 Yo	ar:19 93	
	proposal received from Gary Linde			<u></u>	
	name) Chief Drilling, Inc.		(phone)	16-262-3791	
	at 3837' w/125 sx cement, Open hole				
-	et CIBP at 3825 and dump 2.sx cement				
2nd plug p	ump 300 lbs. hulls, 10 sx gel, 250 sx	cement down 8 5/8".			
	•				
			<u> </u>		
	Stunging Penns	al Received by	Dan Goodr	OW	
•	Prugging Propos	(TECHNICIAN)			
Plugging	Operations attended by Agent?: All	X Part_	Non	ιθ	
Operation	s'Completed: Hour: <u>11:15 a.m</u> .Day:	24 Month:	3Ye	oar:19 <u>93</u> -	
ACTUAL PL	.ugging REPORT lst plug set CIBP at	3825 and dump 2 sx c	ement on top,		
	umped 300 lbs. hulls, 10 sx gel, and 2				
Maximum pr	essure 700 psi and shut in 500 psi.			·	
			PAG	AEIVED	_
 			STATE CORPO	RATION COMMISSION	ŀ
	<u> </u>		MAR	2 9 1993	
	77 1 (O/10 P + O7)				
Remarks:	Used 60/40 Pozmix 8% gel by Allied.	Recovered 2200' of $5\frac{1}{2}$ ' necessary, use BACK	of this tori	ha.Kansas	$\overline{\wedge}$
I ROLL	文文文文文文文文 observe this plugging.			8	M
DATE STA	20~91	Signed Dan	John		
	3-24		TECHNICIAN)		
	> /			FORM CP-	2/