1080084

To:	API NUMBER 15-101 - 20,905-6660
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION	NE/4 , Sec. 22 , T 16 S, R 29 WARK
200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	990 feet from N/% section line
TECHNICIAN'S PLUGGING REPORT	feet from XXVE section line
Operator License # 6735	Lease Name Roberts "B" Well # 1
Operator: Southwestern Energy Prod. Co. Name & 1001 N.W. 63, Su 200 Address Oklahoma City, OK 73116	Well Total Depth 4645 feet 150.96 Conductor Pipe: Size feet
	Surface Casing: Size 5/8 feet 356
Abandoned Oil Well Gas Well Inp	
Other well as hereinafter indicated .	
Plugging Contractor DaMac Drilling, Inc.	License Number 6333
Address Box 1164, Great Bend, KS 67530	
Company to plug at: Hour: 8:00 am Day: 3	1 Month: January Year:19 84
VERBAL PLUGGING ORDERS GIVEN TO John Crowe	
(company name) DaMac Drilling	(phone) 316-792-1353
were: to fill hole withheavy mud and spot cement through drill pipe.	
1st plug at 2145' with 50 sx cement	
2nd plug at 1100' with 50 sx cement	
3rd plug at 400' with 40 sx cement solid bridge	5
4th plug hulls - plug at 40' cement to su 6th plug to circulate rathole with 15 sx cem 10 sx cement.	
Plugging Operations attended by Agent?: All_	PartNoneX
Operations Completed: Hour: 10:00 pm Day:	31 Month: January Year:19 84
ACTUAL PLUGGING REPORT 1st plug at 2145' wi	th 50 sx cement, 2nd plug at 1100' with
50 sx cement, 3rd plug at 400' with 40 sx ce	ement, 4th & 5th plugs - solid bridge - hulls
plug at 40' cement to surface with 10 sx	· · · · · · · · · · · · · · · · · · ·
15 sx cement. 7th plug to circulate mousehol	e with 10 sx cement.
Remarks: Use 60/40 Pozmix, 2% gel 3%	cc. by Allied.
I hereby certify that the above plugging	instructions were given as herein stated
and that I (XXXX / did not) observe this plugg.	·
, , , , , , , , , , , ,	

Signed_

FORM CP-2/3 Rev. 9-82

RECEIVED

RECEIVED

RECEIVED

RECEIVED

FEB 0 8 1984

CONSERVATION DIVISION

Wighita, Kansas