1 070367	API NUMBER 15-101-21,397-6000
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING	
2CO COLORADO DERBY BUILDING WICHITA, KANSAS 67202	330feet from \$ section line
TECHNICIAN'S PLUGGING REPORT	1650 feet from E section line
Operator License # 9482	Lease Name James Well #
Operator: National Petroleum Rese	
Name& Address 260 North Rock Road, Su	
Wichita, KS 67206	Conductor Pipe: Sizefeet
	Surface Casing: \$1ze 8 5/8 feet 257
Abandoned Oll Well Gas W	ell Input Well SMD Well D&A_X
Other well as hereinafter indicate	
	11ing Company 5302 License Number
Address 1720 Kansas State Bank	
	Day: 8 Month: 7 Year:19 87
Plugging proposal received from 1	
• /	
(company name) Red Tiger Drilli	ng Company (phone)316-263-1201 and spot cement through drill pipe Elevation 2801 KB Anhydrite 2194-2221
1st plug at 2220' with 50 sx ceme	nt, 2nd plug at 1700' with 80 sx cement,
3rd plug at 1300° with 40 sx ceme	nt, 4th plug at 240° with 40 sx cement,
5th plug at 40° with 10 sx cement	, 6th plug to circulate rathole with 15 sx cement.
Plug	ging Proposal Received by Glenn Barlow
	(TECHNICIAN)
	gent?: AllPartNone_X
Operations Completed: Hour: $11:30$	a.mpay: 8 Month: 7 Year:19 87
ACTUAL PLUGGING REPORT 1st plug a	t 2220' with 50 sx cement,
2nd plug at 1700 with 80 sx ceme	nt,
2nd plug at 1700 with 80 sx ceme	nt,
2nd plug at 1700 with 80 sx ceme	nt, RECEIVED STATE CORPORATION COMMISSION
2nd plug at 1700' with 80 sx ceme 3rd plug at 1300' with 40 sx ceme 4th plug at 240' with 40 sx cemen	nt, RECEIVED STATE COMPORATION COMMISSION 1t, 11, 11, 1987
2nd plug at 1700' with 80 sx ceme 3rd plug at 1300' with 40 sx ceme 4th plug at 240' with 40 sx cemen	nt, RECEIVED STATE COMPORATION COMMISSION Lt, STATE COMPORATION DIVISION CONSERVATION DIVISION
2nd plug at 1700' with 80 sx ceme 3rd plug at 1300' with 40 sx ceme 4th plug at 240' with 40 sx cemen 5th plug at 40' with 10 sx cement 6th plug to circulate rathole wit Remarks: Used 60/40 Pozmix 2% gel	nt, nt, STATE CORPORATION COMMISSION STATE CORPORATION COMMISSION (t), (t), (onservation Sivision Wignita, Kansas by Halliburton.
2nd plug at 1700° with 80 sx ceme 3rd plug at 1300° with 40 sx ceme 4th plug at 240° with 40 sx cemen 5th plug at 40° with 10 sx cement 6th plug to circulate rathole wit Remarks: Used 60/40 Pozmix 2% gel	h 15 sx cement. BY Halliburton. Int, HECCIVED STATE CORPORATION COMMISSION STATE CORPORATION SIVISION Wichita, Kansas BY Halliburton. Iption is necessary, use BACK of this form.)
2nd plug at 1700' with 80 sx ceme 3rd plug at 1300' with 40 sx ceme 4th plug at 240' with 40 sx cemen 5th plug at 40' with 10 sx cement 6th plug to circulate rathole wit Remarks: Used 60/40 Pozmix 2% gel	h 15 sx cement. BY Halliburton. Int, HECCIVED STATE CORPORATION COMMISSION STATE CORPORATION SIVISION Wichita, Kansas BY Halliburton. Iption is necessary, use BACK of this form.)

FORM CP-2/3 Rev.01-84