

10-4

1 030983

API NUMBER 15- 101-21,487-00-00

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

SE SW SW, SEC. 23, T 19 S, R 29 WAE
330 feet from S section line
4290 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5063
Operator: Energy Exploration, Inc.
Name & Address 1002 South Broadway
Wichita, KS 67211

Lease Name Helena Well # 1
County Lane 130.00
Well Total Depth 4000 feet
Conductor Pipe: Size feet
Surface Casing: Size 8 5/8 feet 284

Abandoned Oil Well Gas Well Input Well SMD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Blue Goose Drilling Company Inc. License Number 5104
Address Box 1413, Great Bend, KS 67530

Company to plug at: Hour: 9:30 p.m. Day: 3 Month: 10 Year: 19 88

Plugging proposal received from Martin Miller
(company name) Blue Goose Drilling Company Inc. (phone) 316-792-5633
Elevation 2846'

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2172-2198'
1st plug at 2170' with 50 sx cement, 2nd plug at 1330' with 80 sx cement,
3rd plug at 330' with 50 sx cement, 4th plug at 40-0' with 10 sx cement,
5th plug to circulate rathole with 15 sx cement,
6th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Steve Durrant
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 1 a.m. Day: 4 Month: 10 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug at 2170' with 50 sx cement
2nd plug at 1330' with 80 sx cement,
3rd plug at 330' with 50 sx cement,
4th plug at 40-0' with 10 sx cement,
5th plug to circulate rathole with 15 sx cement,
6th plug to circulate mousehole with 10 sx cement.

RECEIVED
STATE CORPORATION COMMISSION
OCT 5 1988
10-5-88
CONSERVATION DIVISION
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by B.J. Titan.
(If additional description is necessary, use BACK of this form.)

INVOICED observe this plugging.

Signed Steve Durrant
(TECHNICIAN)

DATE 10-10-88
INV. NO. 22555