TO:

STATE CORPORATION COMMISSION **CONSERVATION DIVISION - PLUGGING**

130 SOUTH MARKET, SUITE 2078

WICHITA, KANSAS 67202

API Well Number: 15-101-21810-00-00

Spot: NESESE

Sec/Twnshp/Rge: 6-19S-30W

990 feet from S Section Line,

Surface Casing Size: 8.625

330 feet from E Section Line

Lease/Unit Name: WHITING TRUST UNIT A

Well Number: 1-6

County: LANE

Total Vertical Depth: 4650 feet

Operator License No.: 5003

Op Name: MCCOY PETROLEUM CORPORATION Address: 453 S. WEBB RD. STE 310 PO BOX 7802

WICHITA, KS 67278

feet: 234

*\$151.1*3

Well Type: DH

UIC Docket No:

Date/Time to Plug: 05/04/2003 5:30 PM

Plug Co. License No.: 6039

Plug Co. Name: L.D. DRILLING, INC.

Proposal Revd. from: DORAN MARGHEIM

Company: L.D. DRILLING, INC.

Phone: (620) 793-3051

Proposed 1ST PLUG AT 2250' WITH 50 SX CMT. 2ND PLUG AT 1330' WITH 80 SX CMT. 3RD PLUG AT 650' WITH 40 SX Plugging CMT. 4TH PLUG AT 260' WITH 40 SX CMT. 5TH PLUG AT 40' WITH 10 SX CMT. 6TH PLUG TO CIRCULATE

RAT HOLE WITH 15 SX CMT. NO MOUSE HOLE. Method:

Plugging Proposal Received By: RICHARD LACEY

WitnessType: Plugging Operations Were Not Witnessed

Date/Time Plugging Completed: 05/04/2003 8:30 PM

KCC Agent: RICHARD LACEY

Actual Plugging Report:

IST PLUG AT 2250' WITH 50 SX CMT. 2ND PLUG AT 1330' WITH 80 SX CMT. 3RD PLUG AT 650' WITH 40 SX CMT. 4TH PLUG AT 260' WITH 40 SX CMT. 5TH PLUG AT 40' WITH 10 SX CMT. 6TH PLUG TO CIRCULATE RAT HOLE WITH 15 SX CMT. NO MOUSE HOLE.


> RECEIVED MAY 1 3 2003 KCC WICHITA

Remarks:

USED 60/40 POZMIX 6% GEL 1/4# FLO SEAL BY ALLIED.

Plugged through: DP

District: 01



Richard W. Facey (TECHNICIAN)