

1 120005

7-23-87

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-165-20,865-00-00

NW NW NE, SEC. 28, T 16 S, R 17 W/E

4950 feet from S section line

2310 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5140

Lease Name Roth "E" Well # 1

Operator: Frontier Oil Company

County Rush 118.79

Name &

Address 1720 Kansas State Bank Building

Well Total Depth 3655 feet

Wichita, KS 67202

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 336

Abandoned Oil Well \_\_\_\_\_ Gas Well  Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ O&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Frontier Oil Company License Number 913-483-5348

Address 1720 Kansas State Bank Building, Wichita, KS 67202

Company to plug at: Hour: 12:30 p.m. Day: 23 Month: 7 Year: 19 87

Plugging proposal received from Richard Parker

(company name) Frontier Oil Company (phone) 913-483-5348

were: Perforated at 3050-53, 3028-38'

1st plug pump down 4 1/2" with 35 bbls cement slurry and 300 lbs. hulls,

2nd plug pump 35 bbls cement slurry and 15-20 bbls cement slurry between 8 5/8" and 4 1/2" casing.

Plugging Proposal Received by Duane Rankin

(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 1:30 p.m. Day: 23 Month: 7 Year: 19 87

ACTUAL PLUGGING REPORT 1st plug pumped in the 4 1/2" with 75 sx light cement, 300 lbs. hulls,  
and 75 sx light cement. Maximum pressure 600 psi and shut in 300 psi.

2nd plug pumped 100 lbs. hulls and 35 sx light cement between the 8 5/8" and the 4 1/2" casing.  
Shut in 100 psi.

Used ready mix cement to fill 4 1/2" and annulus which dropped 70'. Work done 7/24/87.

Remarks: Used light cement by Allied. No recovery.

(If additional description is necessary, use BACK of this form.)

I observed this plugging.

DATE 7-29-87

INV. NO. 17642

Signed 07-29-1987

Duane Rankin  
(TECHNICIAN)