## TYPE

SIDE ONE

AFFIDAVIT OF COMPLETION FORM

Two (2) copies of this form shall be filed with mission, 200 Colorado Derby Building, Wichita, Kansa days after the completion of a well, regardless of he Attach separate letter of request if the inform If confidential, only file one copy. Information on record and Side Two will then be held confidential.  Applications must be made on dual completion, c	s 67202, within thirty (30) ow the well was completed. ation is to be held confidential.  Side One will be of public
injection and temporarily abandoned wells.  Attach one copy only wireline logs (i.e. electroneutron log, etc.). (Rules 82-2-105 & 82-2-125) KC	ical log, sonic log, gamma ray
LICENSE # 5050 EXPIRATION DATE	6-30-83
OPERATOR Hummon Corporation	API NO. 15-007-21,585 -0000
ADDRESS 400 One Main Place	COUNTY Barber
Wichita, Kansas 67202	FIELD HILDER MCREYNOLDS
** CONTACT PERSON Wilber Berg PHONE 316/263-8521	PROD. FORMATION Douglas
PURCHASER Getty Trading & Transportation	LEASE Chapin
ADDRESS 330 Broadway Plaza, 105 S. Broadway	WELL NO. 1-36
Wichita, KS 67202	WELL LOCATION C NW SE
DRILLING Big-H Drilling, Inc.	1980 Ft. from south Line and
CONTRACTOR ADDRESS 400 One Main Place	1980 Ft. from east Line of
Wichita, Kansas 67202	the SE (Qtr.) SEC 36 TWP 31S RGE 11 (W).
PLUGGING NA	WELL PLAT (Office Use Only)
CONTRACTOR · ADDRESS	KCC /
	KGS
TOTAL DEPTH 4745° PBTD 4300°	SWD/REP_
SPUD DATE 3/29/83 DATE COMPLETED 4/7/83	36 PLG
ELEV: GR 1630 DF 1641 KB 1643	
DRILLED WITH (CABLE) (ROTARY) (AIR) TOOLS.	
DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE C-21.045	
Amount of surface pipe set and cemented 218	DV Tool Used? No .
THIS AFFIDAVIT APPLIES TO: (Circle ONE) (Oil) Gas, Injection, Temporarily Abandoned, OWWO. Other	Shut-in Gas, Dry, Disposal,
ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATION AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.	ONS PROMULGATED TO REGULATE THE OIL STATE CORPORATION COMMISSION
•	MAY 1 9 1983
<u>A F F I D A V I T</u>	CUNSERVALUM INVISION
Wilber Berg , be	ing of lawful agenthemely certifies
I am the Affiant, and I am familiar with the co The statements and allegations contained therein are	ntents of the foregoing Affidavit.
	Wille Do Derg
SUBSCRIBED AND SWORN TO BEFORE ME this _ 9th	day of May
19 83 .	*
SANDRA L. MENDOZA	
STATE NOTARY PUBLIC SEDGWICK COUNTY, KANSAS FEBRUARY 13, 1986	(NOTARY PUBLIC)

<sup>\*\*</sup> The person who can be reached by phone regarding any questions concerning this information.

SIDE TWO		<b>~</b>	ACO-1 WELL H	
OPERATOR Hummon Corporation LE	ASE <u>Chap</u>	in S	EC. 36 TWP.31	RGE 11 (W) -
FILL IN WELL INFORMATION AS	REQUIRED:	WELL NO.	1-36	
Show all important zones of porosity and contants thereof; cored	intervals, and all drill-	tem tests, in-	SHOW GEOLOGICAL MAP OR OTHER DESCRIPTIVE	KERS, LOGS RUN, E INFORMATION.
cluding depth interval testics, cushion used, time tool open, flowing	ond shut-in pressures,	and recoveries.	NAME	DEPTH
FORMATION DESCRIPTION, CONTENTS, ETC.		BOTTOM	Name	
Check if no Drill Stem Tests Run.			ELECT. LOG Ind. Cv.	rops 2656 -1013
DST #1: 3703-3715'	Fp 90_1	01/112-12:		2709 -1062
OP 30/30/30/45	SIP 1284		Tarkio LM	2856 -1213
GTS 10" into 2nd opening Ga. 20" 12,500 CFG, 30" 12,500 CFG	HP 1781		Elgin Sh.	3485 -1842
	.   hr 1/01	1770	Heebner	3654 -2011
Rec. 120' HO&GCM, 350' GMO	İ		Douglas SH	3752 -2109
DOM 40. 1/40 1/4751	FP 70-3	0/70-30	Lansing	3824 -2183
DST #2: 4460-4475'	SIP 535-		Miss.	4454 -281
OP 30/45/30/60	HP 2247	•	Kindh.	4596 -295
Rec. 30' 0&GCM	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	2230	Viola	4706 -306
nom #2. 4566 4590!	FP 42-4	2/42-42	LTD	4746
DST #3: 4566-4580' OP 30/45/30/45	SIP 760-	l ·	1	
Rec. 15' mud	HP 2879		]	
Rec. 13 mad	1			
	1			
		20		
Sand	0	38		
Red Rock & Red Beds	38	220		
Red Beds	220	261		
Shale	261	1330		
Shale & Lime	1330	2368 2611		
Lime & Shale	2368	3042	1	
Shale & Lime	2611 3042	3042 3263	OFI F	ASED
Lime & Shale	3263	3786	Ler	] ·-
Shale & Lime	3786	4072	1	0 1095
Lime & Shale	4072	4272	MAY	8 <b>19</b> 85
Shale & Lime	4272	4402		
Lime & Shale Chert	4402	4480	FROM CO	NFIDENTIAL
_	4480	4580	'''	
Lime Shale & Lime	4580	4645	1	1
Lime & Shale	4645	4745		
RTD	1	4745		
If additional space is needed use Page	2. Side 2			
III additional space is needed use rage	z, brue z	L	1	1

Purpose of string	Size hole drifted	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
Surface	12 1/4"	8-5/8	23#	.218	Common	150	2% gel 3%cc
Production	7 7/8"	5 1/2	14#	4589	60/40 Poz	200	2% gel, 10% salt, 3/4 of 1% lo-mar-d
							5# gils. per sx. 500 gal. mud sweep

LINER RECORD			PERFORATION RECORD				
Top, ft.	Bettom, ft.	Socks coment	Shots per ft.	Size & type	Depth interval		
			2 shots/ft	SSB	4463 - 44691		
•	TUBING RECO	RD	4 shots/ft	SSB	3705 - 3710		
Size	Setting depth	Packer set at					
2-3/8"	3757'						

	ACID,	FRACTURE, SHOT,	CEMENT SQUEE	E RECORI	)			
Amount and kind of material used				Depth interval treated				
Acidize w/1000 g	als acid						4463 - 4469	t
Frac w/pur-gel,	23,250 gals	(7500# 20/40		w/KCL # 10/20			4463 - 4469	
?)Acidize w/2500 g )Acidize w/250 ga	als Mod-202 ls 15% MA w	Acid /acid on bott	om				3705 – 3710	,
Date of first production May 6, 1983		Producing method iflower pumpi		ft, etc.)		Grav	ity 36°	
Estimated Production -I.P.	<b>6</b> ii 50	Gos bbis.	MCF	Water o	26		Gas-oil ratio	CFPB
Disposition of gos (vented, use used on				Perfo	ration	s 3	705 - 3710'	