

4-060869

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

4-22

API Number: 15-009-20,767-0000
70' W. of
NE SW SE / 4 SEC. 27, 16 S, 11 W
990 feet from S section line
1720 feet from E section line

Operator license# 6412

Lease: Burmeister Well # 2

Operator: Sid Tomlinson

County: Barton 110.98

Address: 424 NW 42nd St.
Oklahoma City, Ok 73118

Well total depth 3415 feet
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 365 feet

Aband. oil well X, Gas well , Input well , SWD , D & A

Plugging contractor: Co Tools License#

Address:

Company to plug at: Hour: 10:00 A.M. Day: 22 Month: April Year: 1996

Plugging proposal received from: Jim Line

Company: Consultant for Sid Tomlinson Phone: 405-521-1852

Were: Order 175 sxs 60/40 posmix - 8% gel - 15 sxs gel and hulls.

KANSAS
RECEIVED
MAY 31 1996
4-31-96

Plugging Proposal Received by: Herb Deines

Plugging operations attended by agent? All[], Part[], None[X]

Completed: Hour: 12:00 A.M., Day: 22, Month: April, Year: 1996

Actual plugging report: 8 5/8" to 365' w/225 sxs. 5 1/2" to 3414' with 125 sxs with cement to 2850' per bond log. Squeezed hole at 568' with 225 sxs. Tied onto production casing and pumped 50 sxs cement with 400# hulls, 15 sxs gel and 80 sxs cement. Max. P.S.I. 500#. S.I.P. 250#. Tied onto annulus and pumped 50 sxs cement with 100# hulls. Max. P.S.I. 300#. S.I.P. 200#. Tied back onto production casing. Pumped 5 sxs cement. Max. P.S.I. 1000#. S.I.P. 500#.

Remarks: Allied Cementing.
Condition of casing(in hole): GOOD X BAD Anhy.plug: YES X NO
Bottom plug(in place): YES , CALC X, NO Dakota plug: YES X, NO
Plugged through TUBING , CASING X. Elevation: 1936 GL

INVOICED
I did not [X] observe the plugging.

Herb Deines
(agent)
Form CP-2/3

DATE MAY 06 1996
INV. NO. 45530

4-22