		API NUMBER 15- 165-21,236-00-00 1
TATE CORPORATION COMMISSION ONSERVATION DIVISION - PLUGGING SECTION OO COLORADO DERBY BUILDING		SE SE NE , SEC. 20 , T 16 S, R 17 W N SE Corner of 2970 feet from MV8 section 1 in
WICHITA,	KANSAS 67202	W SE Corner of
TECHNICIA	N'S PLUGGING REPORT	330 feet from XXX section in
	license #5198	tease Name Mermis Well # 1
Operator: Name& Address	A. Scott Ritchie	CountyRush
	125 North Market, Suite 950	Well Total Depth 3560 //5.70 fe
	Wichita, KS 67202	Conductor Pipe: Size feet
		Surface Casing: Size 8 5/8 feet 1133
Abandone	1 Oil WellGas Well	Input Well SWD Well D&A_X
Other we	II as hereinafter indicated	
		License Number 6033
riugging	617 Union Center Building, Wich	nita, KS 67202
		24 Month: July Year: 19 84
Plugging	proposal received from	Bud Wenrich
(company	name) Murfin	(phone) 316-267-324
	o fill hole with heavy mud and s	
	g at 1170° with 50 sx cement	
	g at 540° with 40 sx cement	
3rd plu	solid bridge	to surface with 10 sx cement
	g to circulate rat hole with 15	
		oposal Received by PRALITHAN
Plugging	Operations attended by Agent?:	AllPartNone_X
	o ilakidi Hawaa [[*/[[DMD sv	· 74 Month! JULY Tear:1904
		: 24 Month: July Year:1984
ACTUAL F	PLUGGING REPORT 1st plug at 1170	' with 50 sx cement, 2nd plug at 540' with 40
actual F	PLUGGI NG REPORT <u>lst plug at 1170</u> 3rd & 4th plugs - solid bridge	' with 50 sx cement, 2nd plug at 540' with 40 - hulls - plug at 40' cement to surface wi
actual F	PLUGGING REPORT 1st plug at 1170	'with 50 sx cement, 2nd plug at 540' with 40 - hulls - plug at 40' cement to surface wi
actual f	PLUGGI NG REPORT <u>lst plug at 1170</u> 3rd & 4th plugs - solid bridge	'with 50 sx cement, 2nd plug at 540' with 40 - hulls - plug at 40' cement to surface wi hole with 15 sx cement. RECEIVED
cement,	PLUGGI NG REPORT <u>lst plug at 1170</u> 3rd & 4th plugs - solid bridge	'with 50 sx cement, 2nd plug at 540' with 40 - hulls - plug at 40' cement to surface wi hole with 15 sx cement. RECEIVED
cement,	PLUGGI NG REPORT <u>lst plug at 1170</u> 3rd & 4th plugs - solid bridge	with 50 sx cement, 2nd plug at 540' with 40 - hulls - plug at 40' cement to surface with hole with 15 sx cement. RECEIVED STATE CORPORATION COMMISSION
cement,	3rd & 4th plugs - solid bridge ement, 5th plug to circulate rat	with 50 sx cement. 2nd plug at 540' with 40 - hulls - plug at 40' cement to surface with hole with 15 sx cement. RECEIVED STATE CORPORATION COMMISSING ON Allied CONSERVATION DIVISION
cement,	3rd & 4th plugs - solid bridge ement, 5th plug to circulate rat	with 50 sx cement. 2nd plug at 540' with 40 - hulls - plug at 40' cement to surface with hole with 15 sx cement. RECEIVED STATE CORPORATION COMMISSION AUG 01 1984 CONSERVATION DIVISION
cement,	3rd & 4th plugs - solid bridge ement, 5th plug to circulate rat	with 50 sx cement. 2nd plug at 540' with 40 - hulls - plug at 40' cement to surface with hole with 15 sx cement. RECEIVED STATE CORPORATION COMMISSION OF Allied. CONSERVATION DIVISION Wichita, Kansas Is necessary, use BACK of this form.
cement, 10 sx c	Used 60/40 Pozmix 2% gel 3% cc b	with 50 sx cement. 2nd plug at 540' with 40 - hulls - plug at 40' cement to surface with hole with 15 sx cement. RECEIVED STATE CORPORATION COMMISSION OF Allied. CONSERVATION DIVISION Wichita, Kansas Is necessary, use BACK of this form.
cement,	Used 60/40 Pozmix 2% gel 3% cc b	with 50 sx cement. 2nd plug at 540' with 40 - hulls - plug at 40' cement to surface with hole with 15 sx cement. RECEIVED STATE CORPORATION COMMISSION OR - O I - IC/84 AUG 01 1984 CONSERVATION DIVISION Wichita, Kansas Is necessary, use BACK of this form.)