Form CP-3 Rev. 6-26-62

## KANSAS

## STATE CORPORATION COMMISSION

## CONSERVATION DIVISION AGENT'S REPORT

J. P. Roberts Administrator 500 Insurance Building Wichita 2, Kansas

Hole filled with sand to 2600° and cemented with 5 sacks.  Hole filled with mud to 160°. Rock bridge set from 160° to 150° and hole cemented with 25 sacks. Hole filled with mud to 40°. Rock bridge set from 40° to 30° and hole	Operator's Fu	ll Name Charles	Gould		
Location N/2 NW NE Sec. 29 Twp. 16 Rge. 1 (E) (W) X  County Saline Total Depth 2660°  Abandoned Oil Well Cas Well Input Well SWD Well D&A X  Other well as hereafter indicated:  Plugging Contractor: Art Lamb Casing Pulling Co.  Address: 2809 King, Hutchinson, Kansas Incense No. 440  Operation Completed: Hour 3 FM Day 28 Month November Year 1967  The Above well was plugged as follows:  Hole filled with sand to 2600° and cemented with 5 sacks.  Hole filled with mud to 160°. Rock bridge set from 160° to 150° and hole cemented with 25 sacks. Hole filled with mud to 40°. Rock bridge set from 40° to 30° and hole cemented to base of cellar with 10 sacks.	Complete Addre	ess: 5828 N. Broadway, Wichits	, Kansas 67219		
Location N/2 NW NE Sec. 29 Twp. 16 Rge. 1 (E) (W) X  County Saline Total Depth 2660°  Abandoned Oil Well Gas Well Input Well SWD Well D&A X  Other well as hereafter indicated:  Plugging Contractor: Art Lamb Casing Pulling Co.  Address: 2809 King, Hutchinson, Kansas License No. 440  Operation Completed: Hour 3 FM Day 28 Month November Year 1967  The Above well was plugged as follows:  Hole filled with mud to 2600° and cemented with 5 sacks.  Hole filled with mud to 160°. Rock bridge set from 160° to 150° and hele cemented with 25 sacks. Hole filled with mud to 40°. Rock bridge set from 40° to 30° and hele cemented to base of cellar with 10 sacks.	Lease Name	Karber	Well No	1	
Abandoned Cil Well Gas Well Input Well SWD Well Da A X  Other well as hereafter indicated:  Plugging Contractor: Art Lamb Casing Pulling Co.  Address: 2809 King, Hutchinson, Kansas License No. 440  Operation Completed: Hour 3 FM Day 28 Month November Year 1967  The Above well was plugged as follows:  Hole filled with sand to 2600° and cemented with 5 sacks.  Hole filled with mud to 160°. Rock bridge set from 160° to 150° and hole cemented with 25 sacks. Hole filled with mud to 40°. Rock bridge set from 40° to 30° and hole cemented to base of cellar with 10 sacks.	Location	·			
Other well as hereafter indicated:  Plugging Contractor: Art Lamb Casing Pulling Co.  Address: 2809 King, Hutchinson, Kansas License No. 440  Operation Completed: Hour 3 FM Day 28 Month November Year 1967  The Above well was plugged as follows:  Hole filled with sand to 2600° and cemented with 5 sacks.  Hole filled with mud to 160°. Rock bridge set from 160° to 150° and hole cemented with 25 sacks. Hole filled with mud to 40°. Rock bridge set from 40° to 30° and hole cemented to base of cellar with 10 sacks.					
Plugging Contractor: Art Lamb Casing Pulling Co.  Address: 2809 King, Hutchinson, Kansas License No. 440  Operation Completed: Hour 3 FM Day 28 Month November Year 1967  The Above well was plugged as follows:  Hole filled with sand to 2600° and cemented with 5 sacks.  Hole filled with mud to 160°. Rock bridge set from 160° to 150° and hole cemented with 25 sacks. Hole filled with mud to 40°. Rock bridge set from 40° to 30° and hole cemented to base of cellar with 10 sacks.	Abandoned Oil	WellGas WellInput	WellSWD Wel	11D & AX	
Plugging Contractor: Art Lamb Casing Pulling Co.  Address: 2809 King, Hutchinson, Kansas License No. 440  Operation Completed: Hour 3 FM Day 28 Month November Year 1967  The Above well was plugged as follows:  Hole filled with sand to 2600° and cemented with 5 sacks.  Hole filled with mud to 160°. Rock bridge set from 160° to 150° and hole cemented with 25 sacks. Hole filled with mud to 40°. Rock bridge set from 40° to 30° and hole cemented to base of cellar with 10 sacks.	Other well as	hereafter indicated:			
Operation Completed: Hour 3 PM Day 28 Nonth November Year 1967  The Above well was plugged as follows:  Hole filled with sand to 2600° and cemented with 5 sacks.  Hole filled with mud to 160°. Rock bridge set from 160° to 150° and hole cemented with 25 sacks. Hole filled with mud to 40°. Rock bridge set from 40° to 30° and hole cemented to base of cellar with 10 sacks.  I hereby certify that the above DAIC has 1950gged as herein stated.			g Co.		
The Above well was plugged as follows:  Hole filled with sand to 2600° and cemented with 5 sacks.  Hole filled with mud to 160°. Rock bridge set from 160° to 150° and hole cemented with 25 sacks. Hole filled with mud to 40°. Rock bridge set from 40° to 30° and hole cemented to base of cellar with 10 sacks.  I hereby certify that the above DEC tas 1957gged as herein stated.	Address: 2809	King, Hutchinson, Kansas		License No. 440	
Hole filled with sand to 2600° and cemented with 5 sacks.  Hole filled with mud to 160°. Rock bridge set from 160° to 150° and hole cemented with 25 sacks. Hole filled with mud to 40°. Rock bridge set from 40° to 30° and hole cemented to base of cellar with 10 sacks.  ON COMMISSION.  I hereby certify that the above Date has 1950gged as herein stated.	Operation Comp	oleted: Hour 3 PM Day 28	Month November	r Year 1967	
Hole filled with mud to 160°. Rock bridge set from 160° to 150° and hole cemented with 25 sacks. Hole filled with mud to 40°. Rock bridge set from 40° to 30° and hole cemented to base of cellar with 10 sacks.  ON COMMUNICIONAL SALES.  I hereby certify that the above DHC has 1950gged as herein stated.	The Above well was plugged as follows:				
25 sacks. Hole filled with mud to 40°. Rock bridge set from 40° to 30° and hole cemented to base of cellar with 10 sacks.  The filled with mud to 40°. Rock bridge set from 40° to 30° and hole cemented to base of cellar with 10 sacks.  The filled with mud to 40°. Rock bridge set from 40° to 30° and hole cemented to base of cellar with 10 sacks.	Hole filled with sand to 2600° and cemented with 5 sacks.				
cemented to base of cellar with 10 sacks.  On Communication  Thereby certify that the above Diff has 1950gged as herein stated.	Hole filled with mud to 160°. Rock bridge set from 160° to 150° and hole cemented with				
hereby certify that the above will has 1950gged as herein stated.	25 sacks. Hol	e filled with mud to 40°. Rock b	ridge set from 40°	to 30° and hole	
I hereby certify that the above will has 1950gged as herein stated.	cemented to base of cellar with 10 sacks.				
I hereby certify that the above will has 1950gged as herein stated.					
I hereby certify that the above will has 1950gged as herein stated.					
I hereby certify that the above will has 1950gged as herein stated.	***	At 48 484 48			
I hereby certify that the above will has iffigged as herein stated.	<del></del>	ON COMPANY			
DATE 12/1/67 Wichits, Kansas Signed: Well Plugging Supervisor	hereby certi:	fy that the above will has 1950gg	d as herein state	d. 111	
DATE 12/1/61	INV	OICED CONSTITUTION DIVISION WICHITE, Kappan	Signed: Well	Much J. Tomer	
6802-W	DATE	12/1/61 6802-W			