

1052231

TO: 3-9 API NUMBER 15-101-21,755-0000

STATE CORPORATION COMMISSION SE SE SW, SEC. 33, T 16 S, R 27 W

CONSERVATION DIVISION - PLUGGING SECTION 330 RECEIVE FEET FROM SOUTH SECTION LINE

WICHITA STATE OFFICE BLDG., 130 S. MARKET 2167 FEET FROM EAST SECTION LINE

WICHITA, KANSAS 67202

TECHNICIAN'S PLUGGING REPORT

LEASE NAME Anderson Trust WELL # 1  
3-11-98 COUNTY Lane 148.53

OPERATOR LICENSE # 31283 WELL TOTAL DEPTH 4570 FEET

OPERATOR: Rheem Resources, Inc PRODUCTION CSG: SIZE FEET

NAME AND 100 S. Main Suite 505 SURFACE CASING: SIZE 8 5/8" FEET 210

ADDRESS Wichita, Kansas 67202-3738

ABANDONED OIL WELL GAS WELL INPUT WELL SWD WELL D/A X

OTHER WELL AS HEREINAFTER INDICATED

PLUGGING CONTRACTOR Shields Drilling LICENSE NUMBER 5184

ADDRESS 326 Main, P.O. Box 709, Russell, Kansas 67665

COMPANY TO PLUG AT: HOUR: 4:45p.m. DAY 9 MONTH: 3 YEAR: 1998

PLUGGING PROPOSAL RECEIVED FROM Burt Berry

(COMPANY NAME) Shields Drilling Company (PHONE) (913) 483-3141

WERE: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 2090' with 50 sx cement, 2nd plug at 1280' with 80 sx cement

3rd plug at 600' with 40 sx cement, 4th plug at 230' with 40 sx cement

5th plug at 40' with 10 sx cement, 6th plug to circulate rathole with 15 sx cement

7th plug to circulate mousehole with 10 sx PLUGGING PROPOSAL RECEIVED BY Richard Lacey

PLUGGING OPERATIONS ATTENDED BY AGENT?: ALL PART NONE X

OPERATIONS COMPLETED: HOUR: 6:45 p.m. Day: 9 MONTH: 3 YEAR: 1998

ACTUAL PLUGGING REPORT 1st plug at 2090' with 50 sx

2nd plug at 1280' with 80 sx, 3rd plug at 600' with 40 sx

4th plug at 230' with 40 sx, 5th plug at 40' with 10 sx

6th plug to circulate rathole with 15 sx cement

7th plug to circulate mousehole with 10 sx cement

REMARKS: Used 60/40 Pozmix 6% Gel 1/4# FS, by Allied  
(IF ADDITIONAL DESCRIPTION IS NECESSARY, USE BACK OF THIS FORM.)

I (DID NOT) OBSERVE THIS PLUGGING.

SIGNED Richard Lacey  
(TECHNICIAN) FORM CP-2/3

INVOICED

DATE 3-12-98  
INV. NO. 50222

2nd plug at 1350' with 80 sx cement,

3rd plug at 870' with 40 sx cement,

4th plug at 300' with 40 sx cement,

5th plug at 40-0' with 10 sx cement,

6th plug to circulate rathole with 15 sx cement.

Remarks: Used 60/40 Pozmix 6% gel 2% cc 1/4# floseal by Allied.  
(if additional description is necessary, use BACK of this form.)

STATE CORPORATION COMMISSION

APR - 3 1995  
4-6-95

I (DID NOT) OBSERVE THIS PLUGGING.

Signed Steve Klumout  
(TECHNICIAN)

INVOICED  
DATE 4-13-95  
INV. NO. 42573