INV. NO. 3444

TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202		SE NW SW , SEC		R 27 W/R
		N SE Corner of HXX section line W SE Corner of 4290 (test from HXX section line		
TECHNICIAN'S PLUGGING REPORT			feet from NXK se	action line
Operator	license / 6390 & 9067	Lease Name Ander	rson Well #_	1
Namak	McDonald-Wallace Petroleum Co. &	County	Lane	10035
	DaMar Resources, Inc.	Well Total Dept	h 3980	feet
	P. O. Box 70	Conductor Pipe:	S1zefee	Ƞ
	Hays, KS 67601	Surface Casing:	\$1ze_8_5/8feet_	292
Abandoned	Oll WellGas Well	Input Well	SWD Well	D&A X
Other well as hereinafter indicated				
Plugging Contractor Aldebaran Drilling Co., Inc. License Number 5829				
Address Box 18611, Wichita, KS 67207				
Company to plug at: Hour: 2:00 am Day: 20 Month: August Year:1984				
Plugging proposal received from Rex Lutes				
(company name) Aldebaran (phone) 316-685-5372				
were: to fill hole with heavy mud and spot cement through drill pipe				
1st plug at 2100' with 50 sx cement				
2nd plug at 1200' with 50 sx cement				
3rd plug at '340° with 50 sx cement				
solid bridge 4th plug hulls - plug at 40' cement to surface with 10 sx cement				
6th plug to circulate rat hole with 15 sx cement, 7th plug to circulate mouse now with				
-10-sx-ce			(ECHINI CIA	W
	Operations attended by Agent?: Al			
	ns Completed: Hour: 4:00 am Day:			
ACTUAL PLUGGING REPORT 1st plug at 2100' with 50 sx cement, 2nd plug at 1200' with 50 sx				
	3rd plug at 340° with 50 sx cement			
at 40' cement to surface with 10 sx cement, 6th plug to circulate rapply with 15				
sx cement, 7th plug to circulate mouse hole with 10 sx cement. STATE CORPORATION COMMISSION				
			AUG 2 4	1984
			CONSERVATION	
Remarks:	Used 60/40 Pozmix 2% gel 3% cc by	Buie.	Wichita, Ka	insas
Remarks: Used 60/40 Pozmix 2% gel 3% cc by Buie. (If additional description is necessary, use BACK of this form.)				
	d to observe this plugging.	Sland Pa	Ia. Lui	The so
Š -	29-84	Jigned 122	(TECHNICIÁN)	<i>y</i> =

FORM CP-2/3 Rev.01-84