

1 020059

FEB 2 1 1987

API NUMBER 15-101-21,365-0000

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

NW NW NW, SEC. 6, T 17 S, R 29 W/E

4950 feet from S section line

4950 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5886

Lease Name Shay Well # 4

Operator: Chief Drilling Company, Inc.
Name & Address: 151 North Main, Suite 700
Wichita, KS 67202

County Lane 148.82

Well Total Depth 4579 feet

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 433

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor Warrior Drilling Company License Number 5883

Address 151 North Main, Suite 700, Wichita, KS 67202

Company to plug at: Hour: 1 a.m. Day: 21 Month: 2 Year: 19 87

Plugging proposal received from Marion Burris

(company name) Warrior Drilling Company (phone) 316-653-7716

Elevation 2830' GL

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2238-69'

1st plug at 2270' with 50 sx cement, 2nd plug at 1430' with 80 sx cement,

3rd plug at 460' with 50 sx cement, 4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 10 sx cement,

6th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Paul Luthi (TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 4:15 a.m. Day: 21 Month: 2 Year: 19 87

ACTUAL PLUGGING REPORT 1st plug at 2240' with 50 sx cement,

2nd plug at 1430' with 80 sx cement,

3rd plug at 460' with 50 sx cement,

4th plug at 40-0' with 10 sx cement,

5th plug to circulate rathole with 10 sx cement,

6th plug to circulate mousehole with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Allied.

(If additional description is necessary, use BACK of this form.)

INVOICED
Please advise to reserve this plugging.

DATE 2-26-87

Signed Glenn R. Barlow (TECHNICIAN)

INV. NO. 16210