

1 060229

API NUMBER 15- 101-20,972-0000

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION W/2 SW SE, SEC. 6, T 17 S, R 29 W
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

680 feet from N/S section line
2150 feet from W/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5181

Lease Name Dodge 'C' Well # 1

Operator: Donald C. Slawson

County Lane

Name & Address 200 Douglas Building

Well Total Depth 4653 151.22 feet

Wichita, KS 67202

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 450

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Salwson Drilling Co., Inc. License Number 5657

Address 200 Douglas Building, Wichita, KS 67202

Company to plug at: Hour: 6:00 pm Day: 3 Month: May Year: 1984

Plugging proposal received from Ron Rowe

(company name) Slawson (phone) 316-263-3201

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 2200' with 50 sx cement

2nd plug at 1400' with 50 sx cement

3rd plug at 500' with 50 sx cement
solid bridge

4th plug hulls - plug at 40' -- cement to surface with 10 sx cement

6th plug to circulate rathole with 15 sx cement

Plugging Proposal Received by Paul A. Luthie (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 5:00 pm Day: 3 Month: May Year: 1984

ACTUAL PLUGGING REPORT 1st plug at 2200' with 50 sx cement, 2nd plug at 1400' with 50 sx cement, 3rd plug at 500' with 50 sx cement, 4th & 5th plugs - solid bridge - hulls - plug at 40' -- cement to surface with 10 sx cement, 6th plug to circulate rathole with 15 sx cement.

RECEIVED STATE CORPORATION COMMISSION

MAY 11 1984 5-11-84 CONSERVATION DIVISION Wichita, Kansas

Remarks: Use 60/40 Pozmix 2% gel 3% cc by Halliburton
(If additional description is necessary, use BACK of this form.)

INVOICED

DATE 5-15-84

Signed Paul A. Luthie (TECHNICIAN)

INV. NO. 1509

MAY 23 1984