| To: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202 TECHNICIAN'S PLUGGING REPORT |   | API NUMBER 15- 101-21,161.0000        |               |
|--|---|---------------------------------------|---------------|
|  |   | NE NE NW , SEC. 5 , † 17              |               |
|  |   | 2970 feet from #/E section line       |               |
| Operator   | License # 5181  |                                       |               |
| Namat  | Donald C. Slawson   | County Lane                           |               |
|  | 200 Douglas Building  | Well Total Depth 4580                 |               |
|  | Wichita, KS 67202   | Conductor Pipe: Size                  | feet          |
|  |   |                                       |               |
| Abandoned  | Oli Well Gas Well   | Surface Casing: Size 8 5/8 fee        | 347           |
| Other well   | l as hereinafter indicated                                    | SWD Well                              | D&A_X         |
|  |   | License Number_                       | F/F7          |
| Address 2  | 200 Douglas Building, Bradeway &                              | Douglas, Wichita KS 67202             | 265/          |
|  |   |                                       |               |
| Plugaina a   | roposal received from Glen Cor                                | 28 Month: April Year                  | : 1985        |
|  |   |                                       | <del>-</del>  |
| wara. to f   | ill hole with heavy mud and spot                              | (phone) 31                            | 6-263-3201    |
|  |   | cement through drill pipe             |               |
|  | at 2199' with 50 sx cement<br>at 1400' with 60 sx cement      |                                       |               |
|  |   |                                       |               |
|  | at 368' with 50 sx cement solid bridge                        |                                       |               |
|  | hulls - plug at 40 to circulate rat hole with 15 s            |                                       |               |
|  | Plugging Prop   | osai Received by (TECHNICIA           | Eley          |
| Plugging O   | perations attended by Agent?: A                               | -                                     |               |
|  | Completed: Hour: 1:30 pm Day:                                 | 20                                    | <del></del>   |
|  |   | ith 50 sx cement, 2nd plug at 1400'   | 19 85         |
| sx cement  | , 3rd plug at 368' with 50 sx ce                              | ement, 4th & 5th plugs - solid bridg  | with 60       |
|  |   | sx cement, 6th plug to circulate ra   |               |
| 15 sx cem  | ment.   | sx cement, oth plug to circulate ra   | t hole with   |
|  |   | OTATE DOCUMENT                        | PED           |
|  |   | STATE CORPORATIO                      | IN COMMISSION |
| Remarks: IIo   | ed 60/40 Posmin 2% 1 2%                                       | MAY 0.3                               | 2 -1000       |
| <u>. 08</u>  | ed 60/40 Pozmix 2% gel 3% cc<br>(If additional description is | necessary, use BACK of this formed ka | DIVISIONS     |
| الله کر الانتخابی ا  | diffot) observe this plugging.                                | - WIGHER KE                           | insas         |

Signed (TECHNICIAN)

FORM CP-2/3 Rev.01-84