•	1 030426			\mathcal{F}
To:	PORATION COMMISSION	API NUMBER 15-	101-21,172	6000
CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING		NW NW NE , SEC.	<u>15</u> , † <u>1</u>	7 s, R 29 W/K
WICHITA, K	CANSAS 67202	4950	feet from	S section line
TECHNICIAN	N'S PLUGGING REPORT	2310	feet from	E section line
Operator L	1cense / 5151	•		3-15
•	Gear Petroleum Co., Inc.	County	Lane	(Mississippi)
	300 Sutton Place	Well Total Dept	h4	650 feet
	Wichita, KS 67202	Conductor Pipe: Sizefeet		
		Surface Casing:	\$1ze 8 5/8"	feet <u>326</u>
Abandoned	Oli Well Gas Well	input Weli	SWD Well	D&A X
	t as hereinafter indicated			
	Contractor Red Tiger Drilling Com			ber 5302
-	1720 Kansas State Bank Building			
	o plug at: Hour: noon Day:			
	proposal received from			
-	•			0) 016 060 0071
	name) Red Tiger			
	fill hole with heavy mud and spo		III pipe Ain	ydille 220i
	at 2200 with 50 sx cement		· · · · · · · · · · · · · · · · · · ·	- · · · · · · · · · · · · · · · · · · ·
2nd plug a	at 1110' with 50 sx cement			
	at 600 with 40 sx cement			
5th plug h	at 360' with 50 sx cement solid bridge oulls - plug at 40' cement to	surface with 10 sx	cement	
7th plug t with 15 sx	to circulate rat hole lugging Prop	osal Received by	Steve (TECH	Durrant INICIAN)
	Operations attended by Agent?: /	\ Part	N	ione X
	s Completed: Hour: 2:45 pm Day:			
•	UGGING REPORT 1st plug at 2200 w			
	, 3rd plug at 600' with 40 sx cem			
	- solid bridge - hulls - plug at			· · · · · · · · · · · · · · · · · · ·
			dilace with	IO SA CEMENT, 7th
plug to ci	irculate rat hole with 15 sx ceme	nt	SACT OF DAT	TVL)
			I AY S	3/1985
			POsterior and	: 1965 ~
Remarks: <u>I</u>	Used 60/40 Pozmix 2% gel 3% cc by	Allied. s necessary, use <u>BA</u> (CONSTRUZZION	LEWISION 25.Me)
N. V&Q.	GidEnd) observe this plugging.	0 4		-1-
- 6-c	6-85	Signed Ste	y Hai	nont

V. NO. 8344 JUL 1 2 19

FORM CP-2/3 Rev.01-84