

To: **1090559**  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

TECHNICIAN'S PLUGGING REPORT

Operator License # 31142  
Operator: Petroleum Property Services, Inc.  
Name & Address 155 N. Market, Ste. 1010  
Wichita, KS 67202

*6-16* API NUMBER 15- 101-20,838  
NW NE NE, SEC. 13, T 17 S, R 29 W/E  
4950 feet from S section line  
990 feet from E section line  
Lease Name Hazel Eaton Well # 1-13  
County Lane  
Well Total Depth 4619 150.12 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 331

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Allied Cementing License Number \_\_\_\_\_

Address \_\_\_\_\_

Company to plug at: Hour: 10 a.m. Day: 16 Month: 6 Year: 1995

Plugging proposal received from Bill Hammack

(company name) Petroleum Property Services, Inc. (phone) 316-265-3351

work: 4 1/2" at 4617' w/175 sx cement, PBD 4585', Perfs at 4465-68, 4480-86, 4501-04, 4506-09, 4529-31, 4535-37', DV @ 1350' w/250 sx cement to surface

1st plug pump 4 sx hulls and cement to 0'.

Plugging Proposal Received by Steve Durrant  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 10:45 a.m. Day: 16 Month: 6 Year: 1995

ACTUAL PLUGGING REPORT 1st plug pumped down 4 1/2" casing with 4 sx hulls and 256 sx cement.

Maximum pressure 700 psi and shut in 300 psi.

Pressured backside to 400 psi.

Remarks: Used 60/40 Pozmix 8% gel by Allied. No casing recovery.  
(if additional description is necessary, use BACK of this form.)

**INVOICED**

DATE 6-30-95

INV. NO. 43022

Signed [Signature] (TECHNICIAN)