

1 070641

1-30

265

R

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 101-21,425 - 0000

NE SE NW, SEC. 1, T 18 S, R 30 W/E
3630 feet from S section line
2970 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5886

Lease Name Cramer Well # 2

Operator: Chief Drilling Company, Inc.
Name & Address: 350 Kress Energy Center
224 East Douglas
Wichita, KS 67202

County Lane 149.50
Well Total Depth 4600 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 8 5/8 feet 298

Abandoned Oil Well Gas Well _____ Input Well _____ SWD Well _____ D&A _____

Other well as hereinafter indicated _____

Plugging Contractor Chief Drilling Company, Inc. License Number 5886

Address 350 Kress Energy Center, 224 East Douglas, Wichita, KS 67202

Company to plug at: Hour: 10:15 a.m. Day: 30 Month: 1 Year: 19 89

Plugging proposal received from Gary Lindenmuth

(company name) Chief Drilling Company, Inc. (phone) 316-653-4856

were: 4 1/2" at 4593' PBD 4581' Perfs at 4493-4532' Port collar at 2208' w/200 sx lite cem.
1st plug pump 200 lbs. hulls and 150 sx cement in 4 1/2",
2nd plug pump 50 sx cement on backside.

Plugging Proposal Received by Duane Rankin (TECHNICIAN)

Plugging Operations attended by Agent?: All Part _____ None _____

Operations Completed: Hour: 11:45 a.m. Day: 30 Month: 1 Year: 19 89

ACTUAL PLUGGING REPORT 1st plug pumped 400 lbs. hulls, 100 sx ATL down 4 1/2".

Maximum pressure 1000 psi and shut in 800 psi.

2nd plug pumped 5 sx ATL down 8 5/8". Maximum pressure 1000 psi and shut in released to 0 psi.

RECEIVED STATE CORPORATION COMMISSION

FEB 0 1989 2-10-89

Remarks: Used ATL cement by Allied. No casing recovery.

(If additional description is necessary, use BACK of this report)

INVOICED observe this plugging.

DATE 2-8-89

Signed Dan Hodson (TECHNICIAN)

INV. NO. 23886

1-30