| - | | 499373 | | | | |
|----|--|--|----------|---|--|--|
| | To: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202 TECHNICIAN'S PLUGGING REPORT Operator License # 5181 | | | API NUMBER 15- 101-20,828-0000 | | |
| | | | E/2 | E/2 SW , SEC. 34 , T 18 S, R 29 W/6 | | |
| | | | _ | 1320 feet from S section line | | |
| | | | | 4950 feet from E section line | | |
| | | | | Lease Name McWhirter UU Well # 1 | | |
| | Operator: Donald C. Slawson | | • | County Lane /50.80 | | |
| | 11 1 | 200 Douglas Building | • | Well Total Depth 4640 feet | | |
| | VGG1 422 | Wichita, KS 67202 | - | 3 | | |
| | | | • | Surface Casing: Size 5/8 feet 384 | | |
| | | Oli Wall w Cas Wall | - | nput WellD&A | | |
| | | | | | | |
| | | l as hereinafter indicated | | · · · · · · · · · · · · · · · · · · · | | |
| | | | | License Number 6050 | | |
| | Address | Box 347, Chase, KS 67 | 7524 | | | |
| | | | | Month: February Year: 19 85 | | |
| | Plugging | proposal received from | Ron | Hoover | | |
| | (company name) Kelso (phone) 316-938-2457 | | | | | |
| | were: 4 1/2" set at 4639' PBTD 4582' Perfs at 4405, 4401, 4397, 4366, 4342-48, 4292-95 | | | | | |
| | lst plug | sand back to 4240 and dump 4 sy | x cem | ent on top of sand through bailer | | |
| | 2nd plug squeeze well with 3 sx hulls, 15 sx gel, 75 sx cement, 15 sx gel, 1 sack hulls, | | | | | |
| | release 8 5/8" rubber plug and pump 175 sx cement. | | | | | |
| | 2-15-85 | | | | | |
| | | Piucoina Pro | 00058 | Received by Paul A. Luthi Section 2 | | |
| | | , 1299119 | , po s u | (TECHNICIAN) | | |
| | Plugging | Operations attended by Agent?: | AII_ | PartNoneX | | |
| | Operation | s Completed: Hour: 3:00 pm Day: | : 13 | Month: February Year: 19 85 | | |
| | ACTUAL PL | UGGING REPORT 1st plug sanded | d bac | k to 4240° and dumped 4 sx cement on top of | | |
| | sand thro | sand through bailer, 2nd plug squeezed well with 3 sx hulls, 15 sx gel, 75 sx cement, 15 | | | | |
| | | sack hulls, released 8 5/8" rul | | | | |
| | | | | | | |
| | | | | | | |
| | | 1200 not and about in 400 | | | | |
| | Maximum pressure 1200 psi and shut in 400 psi Remarks: Recovered 2500' 4 1/2" casing. Used 60/40 Pozmix 2% gel 3% cc by Allied. | | | | | |
| | Remarks: | (if additional description | is ne | cessary, use BACK of this form.) | | |
| | | did not bobserve this plugging. | | <u> </u> | | |
| | | 2-85 | | Signed Store Munort | | |
| | v. no | | | (TECHNICIAN) | | |
| N/ | v. №U(_ | 2-13 | | FORM CP-2/3 Rev.01-8 | | |