

STATE OF KANSAS
STATE CORPORATION COMMISSION
200 Colorado Derby Building
Wichita, Kansas 67202

WELL PLUGGING RECORD
K.A.R.-82-3-117

API NUMBER 15-101-21,301-000

LEASE NAME Snider

WELL NUMBER 4-15
100' S OF S/2

SPOT LOCATION NW/4 NE/4

SEC. 15 TWP. 17 SRGE. 29 W (E) or (W)

COUNTY Lane

Date Well Completed 3/26/86

Plugging Commenced 3/26/86

Plugging Completed 3/26/86

TYPE OR PRINT
NOTICE: Fill out completely
and return to Cons. Div.
office within 30 days.

LEASE OPERATOR Gear Petroleum Company, Inc.

ADDRESS 300 Sutton Place, Wichita, Ks. 67202

PHONE # (316) 265-3351 OPERATORS LICENSE NO. 5151

Character of Well D & A
(Oil, Gas, D&A, SWD, Input, Water Supply Well)

Did you notify the KCC/KDHE Joint District Office prior to plugging this well? Yes

Which KCC/KDHE Joint Office did you notify? Dodge City, Ks. 67801 - Paul Luthi

Is ACO-1 filed? Yes If not, is well log attached? _____

Producing formation N/A Depth to top _____ bottom T.D. 4,650'

Show depth and thickness of all water, oil and gas formations. **See ACO-1**

OIL, GAS OR WATER RECORDS

CASING RECORD

Formation	Content	From	To	Size	Put in	Pulled out
				<u>8 5/8"</u>	<u>321'</u>	<u>-0-</u>

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used state, the character of same and depth placed, from feet to feet each set.

1st Plug @ 2225' w/50 sx cement; 2nd Plug @ 1300' w/80 sx cement;
3rd Plug @ 360' w/40 sx cement; 4th Plug @ 40' w/10 sx cement;
15 sx cement in rathole (Plugs calculated by displacement)
195 sx 60/40 Pozmix, 6% Gel.

(If additional description is necessary, use BACK of this form.)

Name of Plugging Contractor Red Tiger Drilling Company License No. 5302
Address 1720 KSB Building, Wichita, Kansas 67202

STATE OF Kansas COUNTY OF Sedgwick, ss.

Dan A. Bowles (employee of operator) or
(operator) of above-described well, being first duly sworn on oath, says: That
I have knowledge of the facts, statements, and matters herein contained and
the log of the above-described well as filed that the same are true and
correct, so help me God.

X (Signature) [Signature]

Dan A. Bowles
(Address) 300 Sutton Place, Wichita, KS



SUBSCRIBED AND SWORN TO before me this 4th day of April, 19 86

[Signature]
Notary Public
Mercedith K. Crisp

My Commission expires: 3/30/89

CONFIDENTIAL

04-08-1986
APR - 8 1986

CONSERVATION DIVISION
Wichita, Kansas

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

V

Starting Date 3 15 86 month day year

API Number 15-101-21,301-0000 100' South S/2 NW NE Sec 15 Twp 17 S, Rtg 29 East 4190' West 1980' Ft. from South Line of Section Ft. from East Line of Section

OPERATOR: License # 5151 Name Gear Petroleum Co., Inc. Address 300 Sutton Place City/State/Zip Wichita, KS 67202 Contact Person Jim Thatcher Phone 316-265-3351

Nearest lease or unit boundary line 420' feet County Lane Lease Name Snider Well # 4-15 Ground surface elevation feet MSL Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no Surface pipe by Alternate: 1 2 XXX

CONTRACTOR: License # 5302 Name Red Tiger Drilling Co. City/State Wichita, KS 67202

Well Drilled For: Well Class: Type Equipment: X Oil SWD Infield X Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Expl Wildcat Cable

Depth to bottom of fresh water 200 Depth to bottom of usable water 1100 Surface pipe planned to be set 320 Projected Total Depth 4650 feet Formation Mississippi

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. Date 3/7/86 Signature of Operator or Agent Jim Thatcher Title Production Engineer

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 220 feet per Alt. X(2) XXX This Authorization Expires 9-10-86 Approved By 3-10-86

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

Table with columns for plug depth, feet depth with, and sxs of. Includes entries for 1st through 5th plugs and (2) Rathole with.

NOTE: Agreement between... district office... amount of cement to be used is necessary prior to plugging.

Handwritten notes and signatures: PUSHER Bruce Feibel, TD 4650 FORMATION M155, SURFACE PIPE 8 1/8 @ 328, ANHYDRITE 2225 ELEVATION 2805 KB, STARTING TIME & DATE 3:50 am 3/29/86, COMPLETION TIME & DATE 5:30 pm 3/29/86, 1st PLUG @ 2225 FT. W/ 50 SX, 2nd PLUG @ 1300 FT. W/ 80 SX, 3rd PLUG @ 360 FT. W/ 40 SX, 4th PLUG @ 40 FT. W/ 10 SX, RAT HOLE CIRCULATED W/ 15' CIRC. SX, MOUSE HOLE CIRCULATED W/ SX, WATER WELL PLUGGED W/ SX, CEMENT COMPANY Allied, TECHNICIAN Dan Goodrow

03-31-1986

MAR 31 1986