

1 060043

10-17

1342

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-165-21,537-0000

NE SW SW, SEC. 1, T 19 S, R 20 W/E

990 feet from S section line

4290 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5123

Lease Name Steitz "C" Well # 1

Operator: Pickrell Drilling Company, Inc.

County Rush 140.56

Name & Address 110 N. Market, Suite 205

Well Total Depth 4325 feet

Wichita, KS 67202

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 285

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Pickrell Drilling Company, Inc. License Number 5123

Address 110 N. Market, Suite 205, Wichita, KS 67202

Company to plug at: Hour: 6 a.m. Day: 17 Month: 10 Year: 19 90

Plugging proposal received from Doyle Folkerts

(company name) Pickrell Drilling Company, Inc. (phone) 316-262-8427

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1380-1412'

1st plug at 1430' with 50 sx cement, 2nd plug at 715' with 50 sx cement,

3rd plug at 315' with 50 sx cement, 4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Case Morris  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 8:15 a.m. Day: 17 Month: 10 Year: 19 90

ACTUAL PLUGGING REPORT 1st plug at 1430' with 50 sx cement,

2nd plug at 715' with 50 sx cement,

3rd plug at 315' with 50 sx cement,

4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 15 sx cement.

10-23-90

Remarks: Used 60/40 Pozmix 6% gel by Allied.  
(If additional description is necessary, use BACK of this form.)

INVOICED

DATE 11-6-90

Signed Case Morris  
(TECHNICIAN)

INV. NO. 29840

EFFECTIVE DATE: 10-10-90

State of Kansas

165-21,537-~~2000~~

NOTICE OF INTENTION TO DRILL

Must be approved by the K.C.C. five (5) days prior to commencing well

Expected Spud Date 10 15 90  
month day year

NE SW SW Sec 1 Twp 19 S, Rg 20  East  West

OPERATOR: License # 5123  
Name: Pickrell Drilling Co., Inc.  
Address: 110 N. Market, Suite 205  
City/State/Zip: Wichita, KS 67202  
Contact Person: Don Beauchamp  
Phone: 262-8427

990 feet from South line of Section  
4290 feet from East line of Section  
(Note: Locate well on Section Plat on Reverse Side)

County: Rush  
Lease Name: Steitz 'C' Well #: 1  
Field Name: Wildcat

CONTRACTOR: License #: 5123  
Name: Company Tools

Is this a Prorated Field? yes  no   
Target Formation(s): Cherokee Sand  
Nearest lease or unit boundary: 990'  
Ground Surface Elevation: 2145 feet MSL  
Domestic Well within 330 feet: yes  no   
Municipal well within one mile: yes  no   
Depth to bottom of fresh water: 215'  
Depth to bottom of usable water: 625'  
Surface Pipe by Alternate: 1  2  
Length of Surface Pipe Planned to be set: 275'  
Length of Conductor pipe required: none  
Projected Total Depth: 4300

Well Drilled For: Well Class: Type Equipment:  
 Oil ... Inj ... Infield  Mud Rotary  
... Gas ... Storage ... Pool Ext. ... Air Rotary  
... OWWO ... Disposal  Wildcat ... Cable  
... Seismic; ... # of Holes

Formation at Total Depth: Mississippian  
Water Source for Drilling Operations:  
... well ... farm pond  other

If OWWO: old well information as follows:  
Operator: \_\_\_\_\_  
Well Name: \_\_\_\_\_  
Comp. Date: \_\_\_\_\_ Old Total Depth \_\_\_\_\_

DNR Permit #: N/A  
Will Cores Be Taken?: yes  no   
If yes, proposed zone: \_\_\_\_\_

Directional, Deviated or Horizontal wellbore? yes  no   
If yes, total depth location: \_\_\_\_\_

AFFIDAVIT

250' Alt. II Req.

Exp. 4/5/91

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq.

Pusher 1 1/2" V.C. 40' x 40'

SPUD DATE 10-10-90 INIT. SLB

LENGTH SURFACE PLANNED 320' 3 1/2" 11"

RESERVE PIT STATUS- REMOVE FLUID LINED  
after salt sect. bbls. when done bbls.

RATHOLED AHEAD? Y N SIZE HOLE  
SURFACE PIPE 2 1/2" @ 285' CONDUCTOR  
ANHYDRITE T- 1325' B- 10-2' ELEVATION

TD 1325' FORMATION MISS.

RAN PIPE @ SX DV TOOL SX ALT II DONE Y N

Arbuckle Plug @ \_\_\_\_\_ Ft. W/ SX

Hug./Council @ \_\_\_\_\_ Ft. W/ SX

Anhydrite Base @ 1430 Ft. W/ 50 SX

1/2 Base Anhy. @ 715 Ft. W/ 50 SX

1/2. 1/2 Plug @ \_\_\_\_\_ Ft. W/ SX

Bottom Surface @ 315 Ft. W/ 50 SX

40' Plug @ 40 Ft. W/ 10 SX

RAT HOLE 10 1/2" @ 23' SX MOUSE HOLE W/ 10 SX

WATER WELLS 50 SX (Irr. Well) Pond 50 Hauling X

TECHNICIAN CM DATE 10-15-90

TYPE OF CEMENT 60 42

STARTING TIME 6:00 (AM/PM) DATE 10-17-90

COMPLETION TIME 8:15 (AM/PM) DATE 10-17-90

CEMENT COMPANY Allied