INV. NO. 4299

To: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202		АРІ NUMBER 15- 135-22,598-GUTOS	
		NW NW SW , SEC. 34 , T 20 S, R 22 W, N SE CORNER OF	
		2310 feet from MXX section lin  4720 feet from MXX section lin	
Operator	License / 9310	Lease Name_PfaffWell #1	
	Bentley Oil & Gas Company	County Ness	
	P. O. Box 5012	Well Total Depth 4410 /43.33	
	Wichita Falls, TX 76307	Conductor Pipe: Sizefeet	
		Surface Casing: Size 8 5/8 feet 431	
Abandoned	Oil Well Gas Well	Input Well SWD Well D&A_X	
Other wei	DaMac Drilling Inc	License Number 6333	
		0	
Company 1	to plug at: Hour: $1:00~ m pm$ Day:	9 Month: October Year:19 84	
Plugging	proposal received from	James Ray	
(company	name) DaMac	(phone) 316-692-135	
	fill hole with heavy mud and sp		
	at 1410' with 50 sx cement		
2nd plug	at 810° with 40 sx cement		
3rd plug	at 480° with 40 sx cement		
	solid bridge	to surface with 10 sx cement	
6th plug	to circulate rat hole with IU :	SX CEMENT. IN DING NO SALCHIALE MICHAEL HOLE WIL	
10 ск се	ment Plugging Pi	roposal Received by Ruchard W. Factor (TECHNICIAN)	
Plugging	Operations attended by Agent?:	AllPartNone_X	
		y: 9 Month: October Year:19 84	
	us completed index - 1001 - 1400 pm ca.		
Operatio			
Operatio	LUGGING REPORT 1st plug at 141	0' with 50 sx cement, 2nd plug at 810' with 40	
Operation ACTUAL Page 1	LUGGING REPORT <u>lst plug at 141</u> 3rd plug at 480' with 40 sx cem	0' with 50 sx cement, 2nd plug at 810' with 40 ment, 4th & 5th plugs - solid bridge - hulls - p	
Operation ACTUAL Page 19 cement, at 40 -	Trigging REPORT 1st plug at 141  3rd plug at 480' with 40 sx cem  - cement to surface with 10 sx	0' with 50 sx cement, 2nd plug at 810' with 40 ment, 4th & 5th plugs - solid bridge - hulls - proceedings, 6th plug to circulate rat hole with 10	
Operation ACTUAL Page 19 cement, at 40 -	LUGGING REPORT <u>lst plug at 141</u> 3rd plug at 480' with 40 sx cem	o' with 50 sx cement, 2nd plug at 810' with 40 ment, 4th & 5th plugs - solid bridge - hulls - per cement, 6th plug to circulate rat hole with 10 hole with 10 sx cement.	
Operation ACTUAL Page 19 cement, at 40 -	Trigging REPORT 1st plug at 141  3rd plug at 480' with 40 sx cem  - cement to surface with 10 sx	o' with 50 sx cement, 2nd plug at 810' with 40 ment, 4th & 5th plugs - solid bridge - hulls - per cement, 6th plug to circulate rat hole with 10 hole with 10 sx cement.	
Operation ACTUAL Procession of the ACTUAL Proc	Trigging REPORT 1st plug at 141  3rd plug at 480' with 40 sx cem  - cement to surface with 10 sx	o' with 50 sx cement, 2nd plug at 810' with 40 ment, 4th & 5th plugs - solid bridge - hulls - per cement, 6th plug to circulate rat hole with 10 hole with 10 sx cement.	
Operation ACTUAL Potents,  at 40'- sx cemen	TUGGING REPORT 1st plug at 141  3rd plug at 480' with 40 sx cem  - cement to surface with 10 sx  t, 7th plug to circulate mouse	o' with 50 sx cement, 2nd plug at 810' with 40 ment, 4th & 5th plugs - solid bridge - hulls - proceedings, 6th plug to circulate rat hole with 10 hole with 10 sx cement.  STATE CORPORATION COMMISS	
Operation ACTUAL Potent,  at 40'- sx cemen	Tugging REPORT 1st plug at 141  3rd plug at 480' with 40 sx cem  - cement to surface with 10 sx  t, 7th plug to circulate mouse  Used 60/40 Pozmix 2% gel 3% cc	o' with 50 sx cement, 2nd plug at 810' with 40 ment, 4th & 5th plugs - solid bridge - hulls - proceedings, 6th plug to circulate rat hole with 10 hole with 10 sx cement.  STATE CORREST AND COMMISS OF THE PROPERTY OF THE PR	
Operation ACTUAL Processor  at 40'- sx cemen  Remarks:	Tugging REPORT 1st plug at 141  3rd plug at 480' with 40 sx cem  - cement to surface with 10 sx  t, 7th plug to circulate mouse  Used 60/40 Pozmix 2% gel 3% cc  (If additional description	o' with 50 sx cement, 2nd plug at 810' with 40 ment, 4th & 5th plugs - solid bridge - hulls - processed, 6th plug to circulate rat hole with 10 hole with 10 sx cement.  STATE CORPORATION COMMISS  by Halliburton  construction by Halliburton  is necessary, use BACK of this form. A Marsa:	
Operation ACTUAL Processor  at 40'- sx cemen  Remarks:	Used 60/40 Pozmix 2% gel 3% cc  (If additional description	o' with 50 sx cement, 2nd plug at 810' with 40 ment, 4th & 5th plugs - solid bridge - hulls - proceedings, 6th plug to circulate rat hole with 10 hole with 10 sx cement.  STATE CORPOR THE COMMISS  by Halliburton  CONSTRUCT 2 198-1  CONSTRUCT 2 198-1  The processory, use BACK of this form. The processory	

FORM CP-2/3 Rev.01-84