

To: 1 120595  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION 50' W S/2 S/2, SEC. 16, T 16 S, R 23 W/E  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

7-17 208  
API NUMBER 15-135-21,988-0110  
2690 feet from S section line  
660 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5364  
Operator: Beren Corporation  
Name & Address: 970 Fourth Financial Center  
Wichita, KS 67202

Lease Name Baer Well # 4  
County Ness 144.49  
Well Total Depth 4446 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 339

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_  
Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Beren Corporation License Number 5364  
Address 970 Fourth Financial Center, Wichita, KS 67202

Company to plug at: Hour: 9:30 a.m. Day: 16 Month: 7 Year: 19 91

Plugging proposal received from George Jorgensen

(company name) Beren (phone) 913-628-6101

were: 4 1/2" at 4445' w/200 sx cement, PBTD 4434', Perfs at 4412-19', Hole in casing at 1440'  
1st plug pump 20 sx cement at perfs, 2nd plug pump 20 sx cement at 1440',

3rd plug perforate at 1000' and pump 100 sx cement down 4 1/2",

4th plug pump 100 sx cement down 8 5/8" X 4 1/2" annulus.

RECEIVED  
STATE CORPORATION COMMISSION  
7-24-91  
JUL 24 1991

Plugging Proposal Received by Richard Lacey  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 4:30 p.m. Day: 17 Month: 7 Year: 19 91

ACTUAL PLUGGING REPORT 1st plug ran tubing to 1530' and pumped 10 sx gel and hulls, layed down 2 jts. tubing and pumped 25 sx cement at 1465',

2nd plug pulled tubing and let cement set for 2 hours, tagged cement at 1225', pulled tubing and perforated 4 1/2" casing at 1050', ran tubing back to 1070' and circulated 4 1/2" with 60

sx cement.

3rd plug pumped in 8 5/8" X 4 1/2" annulus with 110 sx cement. Pumping pressure 0-500 psi and

shut in 300 psi. 4th plug pumped in 4 1/2" casing with 35 sx cement. Pumping pressure 0-700 and

Remarks: Used 60/40 Pozmix 6% gel by B.J. No casing recovery. shut in 500

(If additional description is necessary, use BACK of this form.) \_\_\_\_\_ psi.  
I (old / ~~XXXXXX~~) observe this plugging.

INVOICED

DATE 8-8-91  
INV. NO. 32587

Signed Richard Lacey  
(TECHNICIAN)