STATE OF KANSAS STATE CORPORATION COMMISSION

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission

WELL PLUGGING RECORD

. . . .

15:135.30269.0000

State Corporation Commission 212 No. Market		Ness	Coun	ty. Sec. 21	Twp. 16 Rge.	23 (E)	_(W)
Wichita, Kansas NORTH	Location as "N	E/CNWKSWK"			C NE NE		
	Lease Owner	Lease Owner Scherzinger Well No. 1					
	Lease Name Well No. 1 Office Address Well No. 1						
			as Oil, Gas o	or Dry Hole) _			
	Date well com	pleted				19	
)
	Application for Plugging comm	plugging approv	/ed /5/67			19	<u> </u>
1 i i i	Plugging compl		12/67			19	
	Reason for aba	ndonment of we	l or producir	ng formation	depleted		
				-			
Locate well correctly on above Section Plat	menced?	***	the Conser	vation Division	or its agents before	ore plugging was	s com-
Name of Conservation Agent who sup			ssey				
Producing formation			Botto:	m	Total Depth of	Well 4439	Feet
Show depth and thickness of all water	er, oil and gas formation	ns.					
OIL, CAS OR WATER RECOR	EDS .					CASING RECO	RD
FORMATION	CONTENT	FROM	то	SIZE	PUT IN	PULLED OUT	
				8-5/853	274*	none	
				5-1/2**	4431*	31481	
		<u>-</u>					
		<u> </u>			<u> </u>		<u>-</u>
		<u> </u>		<u> </u>	1		
Worked pipe 1 18 sacks mud,	sanded back to checked hole, oose, pulled 5 120 sacks ceme sacks of ceme	shot pipe ; ½" casing. ent and 12	at 3723† Sun Sa	, 33971, 3	2671, 31351		
and pumped 13	Sacks of Cemer						
PLUGGING COMP	LETE			a			
					C. A. C.	<i>> 20</i>	
					000	One One	
				7	18 190		
) -/ e"		
					1/10 0 - C	> >	
	(If additiona	description is nece	ssary, use BAC	K of this sheet)	Wo, KUNJES	10M	
Name of Plugging Contractor	KNIGHT CASING P	ULLING COM	PANY, IN				
Address	CHASE, KANSAS						
STATE OF	Kansas , COU Noel J. Knight	JNTY OFR		owner) or (ow	, ss. mer or operator)	of the above-de	scribed
well, being first duly sworn on oath, above-described well as filed and the	, says: That I have kn at the same are true ar	owledge of the	facts, statem	ents, and matte	ers herein contain	ned and the log	of the
		(Signature)		1/04	Snight	1	
				hase, Kans	(Address)		
Subscribed and Sworn to bef	ore me this 13t	hday of_		October	, 19_1		<i>e</i>
My commission expires February 1	5, 1971			1 argur	et Ine	Notary Pu	blic.

COMPANY: CONTRACTOR: FARM: LOCATION:

COMMENCED: COMPLETED: LEBEN DRILLING, INC. ETAL Leben Drilling, Inc. SCHERZINGER #1 C NE NE SEC. 21-16S-23W NESS COUNTY, KANSAS 10-19-66 11-1-66

0 75	75 105	Surface Soil, Gravel Gravel, Shale
105	932	Shale
932	1175	Blaine
1175	1484	Sand
1484	1820	Shale A.
1820	1837	
1837	2280	Redbed, Shale
2280	2540	Shale, Lime
2540	3085	Lime. Shale
3085	3315	Shale, Chalk Co. 20
3315	3835	Lime. Shale
3835	4442	lime Way
	4442	Lime, Shale Lime RTD - Set 52" Casing, Tengension
•	THE THE PARTY OF T	The state of the s

Set 8 5/8" used surface casing 274' cemented with 185 sacks of Common cement, 2% cc

I, Leslie Kite, do hereby certify that the above and foregoing is a true and correct copy of the log of the Scherzinger 1 Well, located C NE NE of Section 21, Township 16 South, Range 23 West, Ness County, Kansas, as reflected by the records of Leben Drilling, Inc.

Leslie Kite

STATE OF KANSAS)
COUNTY OF BARTON)

Subscribed and sworn to and before me, a Notary Public, in and for Barton County, Kansas, this 4th day of November, 1966.

Ulanda Nichols

My amission Expires: april 1, 1967

SCHERZINGER #1
NE NE
Sec. 21-16S-23W
Ness County, Kansas

WELL COMPLETION REPORT

- 10-14-66 Staked location 75 feet South of center of NE NE Sec. 21-16S-23W, location moved 75 feet from true location to be away from electric lines.
- 10-19-66 Rigging up rotary tools
- 10-20-66 Spudded at 2:00 p.m. Drilled 12½" hole to 275 feet. Ran 12 joints of 8 5/8 inch casing. Set @ 274 feet and cemented with 185 sacks Common cement, 2% cc Plug down @ 8:15 p.m. cement circulated.
- 10-21-66 Drilled plug @ 8:15 p.m. Drilling ahead at 1850 feet; Anhydrite 1800 feet to 1836 feet.
- 10-22-66 Drilling at 2856'
- 10-23-66 Drilling at 2856'; lost circulation; stuck drill pipe; broke bearing housing on drum shaft, waiting on parts
- 10-24-66 Depth of 2856', repaired drawworks, drill pipe stuck
- 10-25-66 Backed off drill pipe at 2542 feet, washing over at 2658 feet
- 10-26-66 On the bank with fish
- 10-27-66 Drilling at 3315 feet
- 10-28-66 Drilling at 3835 feet
- 10-29-66 Drilling at 4120 feet; Elevation 2459' Kelly Bushing
- 10-30-66 Drilling at 4340 feet
- 10-31-66 Drilling at 4442 feet' DST #1 from 4435' to 4442' ISIP 30 min, Open 60 min., FSIP 30 min., Good Blow Throughout Recovered 120 feet gas in Pipe, 640 feet Free Oil, 40 feet Water IBHP 1260#, IFP 95#,FFP 260#, FBHP 1100#
- Ran Lane-Wells Gamma Ray Neutron and Focused-Acoustic Caliper logs, Log TD = 4439'; ran 137 joints of 5½ inch casing set @ 8 feet off bottom; cemented with 100 sacks of 60/40 Posmix with 10% Salt and 1½% cc

5/2"- Casing tally

80 Jts - 2607.84' Black pipe on bottom 54 Jts - 1739.24' Wropped X Tru coat pipe 3 Jts - 97.83' Black pipe on top

4444.71 Total