

1 090466

8-20

API NUMBER 15- 203-20,115-0000

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

SW NW SE, SEC. 36, T 20 S, R 35 W/E
1650 feet from S section line
2310 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5422

Lease Name Uhland "B" Well # 1

Operator: Abercrombie Drilling

County Wichita

Name & Address 150 N. Main, Ste. 801

Well Total Depth 5050 164.13 feet

Address Wichita, KS 67202

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 291

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor Abercrombie RTD, Inc. License Number 30684

Address 150 N. Main, Ste. 801, Wichita, KS 67202

Company to plug at: Hour: 9 p.m. Day: 19 Month: 8 Year: 19 94

Plugging proposal received from Tony Martin

(company name) Abercrombie RTD, Inc. (phone) 316-262-1841

Work: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 2270'

1st plug at 2275' with 50 sx cement, 2nd plug at 1200' with 80 sx cement,

3rd plug at 600' with 40 sx cement, 4th plug at 320' with 50 sx cement,

5th plug at 40' with 10 sx cement,

6th plug to circulate rathole with 15 sx cement.

RECEIVED
STATE CORPORATION COMMISSION

SEP 07 1994

Steve [Signature]
(TECHNICIAN)

Plugging Proposal Received by _____

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 2 a.m. Day: 20 Month: 8 Year: 19 94

ACTUAL PLUGGING REPORT 1st plug at 2275' with 50 sx cement,

2nd plug at 1200' with 80 sx cement,

3rd plug at 600' with 40 sx cement,

4th plug at 320' with 50 sx cement,

5th plug at 40' with 10 sx cement,

6th plug to circulate rathole with 15 sx cement.

Remarks: Used 60/40 Pozmix 6% gel 1/4# floseal by Allied.

(If additional description is necessary, use BACK of this form.)

INVOICED

DATE SEP 12 1994

NO. 41181

Signed [Signature]
(TECHNICIAN)