

15-165-00016-0000

Company: Cardwell Mfg. Co., Inc.
Farm: Dirks No. 1
Total Depth: 3911
Comm. 9-16-52 Comp. 9-29-52
Contractor: E. H. Adair Oil Co.
Casing:
8 5/8 Surface casing at 258'
w/165 sax cement.

Sec. 16 Twp 18S Rge 18W
Loc. NW NW NE
County: Rush
Elevation: 2085 KB
2080 Gr.
Production: Dry

Figures indicate bottom of formations

Lime & Shale	215	Tops:	
Sandy Lime	230	Anhydrite	1215
Shale & Lime	258	Howard Ls.	3112
Shale	330	Topeka Ls.	3171
Sand	393	Heebner Shale	3429
Shale	553	Brown Lime	3458
Dakota Sand	580	Lans-KC	3481
Shale	645	Marmaton (base KC)	3729
Sand	881	Cherty Cong.	3843
Red shale	937	Arbuckle	3881
Shale & Sand	1215		
Anhydrite and lime	1258		
Shale	1982		
Lime & Shale	2215		
Shale & Shells	2235		
Lime 2403	2403		
Shale & Shells	2462		
Lime	2515		
Shale & Shells	3171		
Topeka lime	3429		
Shale, Heebner	3458		
Lime	3782		
Shale & Shells	3815		
Cherty Lime & shale	3843		
Conglomerate	3881		
Arbuckle Dolomite	3911		
total depth	3911 KB		

Certified Correct:

R. Baker

PLUGGING
FILE SEC 16 T 18 R 18W
BOOK PAGE 49 LINE 13

RECEIVED
CONSERVATION COMMISSION
OCT 10 1952
10-10-52
CONSERVATION DIVISION
Wichita, Kansas