

1 090308

R

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 135-22,775-0000  
SE NW, SEC. 11, T 16 S, R 26 W EX

TECHNICIAN'S PLUGGING REPORT

3300 feet from WYS section line  
3300 feet from WYE section line

Operator License # 5144

Lease Name Snyder Well # 1 'A'

Operator: Mull Drilling Company, Inc.

County Ness 148.27

Name & Address P. O. Box 2758

Well Total Depth 4562 feet

Wichita, KS 67201

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 260 ✓

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor DNB Drilling, Inc. License Number 5476

Address 535 North Oliver, Wichita, KS 67208

Company to plug at: Hour: 1:30 pm Day: 24 Month: March Year: 19 85

Plugging proposal received from Jack Baylor

(company name) DNB (phone) 316-687-5471

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 2040' with 50 sx cement

2nd plug at 1230' with 50 sx cement

3rd plug at 330' with 50 sx cement

4th plug <sup>solid bridge</sup> hulls - plug at 40' -- cement to surface with 10 sx cement

6th plug to circulate rat hole with 15 sx cement

Plugging Proposal Received by Robert B. Tarbutton  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 6:00 pm Day: 24 Month: March Year: 19 85

ACTUAL PLUGGING REPORT 1st plug at 2040' with 50 sx cement, 2nd plug at 1230' with 50 sx cement, 3rd plug at 330' with 50 sx cement, 4th & 5th plugs - solid bridge - hulls - plug at 40' -- cement to surface with 10 sx cement.

MAR 29 1985  
3-28-85

Remarks: Used 60/40 Pozmix 2% gel 3% cc by Allied.  
(If additional description is necessary, use BACK of this form.)

~~INVOICED~~ did not observe this plugging.

Signed Robert B. Tarbutton  
(TECHNICIAN)

DATE 4-3-85

REV. NO. 2512 3-2-85 APR 26 1985