KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

Type Test	:				((See Instruc	tions on Re	verse Side)						
	en Flow				Test Date	e:			API	No. 15					
√ De	liverabilt	у			11/24/1					99-20354-	-0000				_
ompany aven R		es, LLC					Lease Westfie	ld				#4-31	Well Num	iber	_
County Location Wallace County SW/4 SW/4				Section 31		TWP 11S		RNG (E/W) 41W		Α		Acres Attributed		_	
ield					Reservoi Niobrara					nering Conn gathering s		(West K	ansas F	Pipeline)	_)
Completion Date 8/2008			Plug Bac 1077'	k Total Dep	th	Packer Set at				To SCC W					
Casing Size Weight 4 1/2" 10.5			Internal I	Diameter	Set at 1092'		Perforations 896'		то 930'		DEC		26:		
ubing Size Weight			Internal Diameter		Set at 912'		Perforations		То		KCC M				
Type Completion (Describe) "Single Gas"			Type Flui Only G	id Production		Pump Unit or Traveling Plune				r? Yes	(No)	oo yy	4CH		
roducing		Annulus Tub	ing))		Carbon Dioxi	ide		% Nitroge	en	· · · · · · · · · · · · · · · · · · ·	Gas Gr	avity - G _g		
ubing ertical D 100'	epth(H)					Pres	sure Taps						Run) (Pro	ver) Size	_
	Buildup:	Shut in1	1/24		0 12 at 1	1:34	(AM) (PM)	Taken 11	1/25	20	12 _{at}	.500" 11:34	KA	M) (PM)	-
Vell on L	•	Started 1	1/25		0 12 at 1		(AM)(PM)					11:34	9	M)(PM)	
···						OBSERVE	D SURFAC	E DATA			Duratio	n of Shut-		Hour	- 's
Static / ynamic roperty	Orifice Size (inches	Ze Prover Pressur		Pressure Differential in	Flowing Temperature t	Well Head Temperature t	Casing Wellhead Pressure (P _w) or (P _t) or (P _c)		Tubing Wellhead Pressure (P _w) or (P ₁) or (P _c)		Duration (Hours)		Liquid Produced (Barrels)		Ì
Shut-In	.3750	" psig (Pr	(ר	Inches H ₂ 0	60		psig 6	psia	psig 6	psia	24		0		-
Flow	.3750	15		7.1	45		2		2		24		0		
						FLOW STF	REAM ATTR	IBUTES							_
Plate Coeffiecient (F _b) (F _p) Mcfd		Circle one: Meter or Prover Pressure psia		Press Extension P _m x h	Extension Fact		Flowing Temperature Factor F _{f1}	Deviation Factor F _{pv}		Metered Flow R (Mcfd)		GOR (Cubic Feel Barrel)		Flowing Fluid Gravity G _m	
·]
_c)² =		: (P _w)	: <u>-</u>	:	(OPEN FL	OW) (DELIV.		') CALCUL P _e - 14.4) +		:		(P _a) ²	² = 0.20 ²	7	
(P _c) ² - (I	P _a) ²	(P _c) ² - (P _w) ²		ose formula 1 or 2 1. $P_c^2 - P_a^2$ 2. $P_c^2 - P_d^2$ ded by: $P_c^2 - P_w^2$	LOG of formula 1. or 2. and divide		Backpressure Curve Slope = "n"		n x L	og [An	itilog	Ope Delive Equals F	pen Flow iverability S R x Antilog (Mcfd)	
															-
pen Flo	 w	Mcfd @ 14.65 psia					Deliverability			Mcfd @ 14.65 psia					
The	undersig	ned authority, erein, and that		ehalf of the	Company,		ne is duly a	uthorized to	o make the			hat he ha	s knowle	dge of	<u>-</u> -
		Witnes	s (if an	y)			-	- V-9	70	For	Company				-
		For Co	mmissi	on		 	-			Che	cked by				_

DEC 2 6 2012

I to request
re true and
ase records
ein named.
y Commissio

Instructions:

If a gas well meets one of the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under OBSERVED SURFACE DATA. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption IS denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31 of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.