

4-29-88

2 040409

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 077-21,173-00-00

NE SE, SEC. 5, T 31 S, R 7 W&E

1980 feet from S section line

660 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5123

Lease Name Burg Well # 1-B

Operator: Pickrell Drilling Company  
Name & Address: 110 N. Market, Suite 205  
Wichita, KS 67202

County Harper 143.81

Well Total Depth 4425 feet

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 278

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Pickrell Drilling Co. License Number 5123

Address Wichita, Ks 67202

Company to plug at: Hour: \_\_\_\_\_ Day: \_\_\_\_\_ Month: \_\_\_\_\_ Year: 19 \_\_\_\_\_

Plugging proposal received from Doyle Folker

(company name) Pickrell Drilling (phone) \_\_\_\_\_

were: 35 sxs @900', 35 sxs @330', 25 sxs @60', 10 sxs in rathole.

Plugging Proposal Received by Steve VanGieson  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 18:00 Day: 29 Month: 4 Year: 1988

ACTUAL PLUGGING REPORT Open ended drill pipe was run to 900' where 35 sxs cement was spotted. The drill pipe was pulled to 330' where 35 sxs cement was spotted in place. The drill pipe was pulled to 60' where 25 sxs cement was circulated to top of surface pipe. The rathole was circulated with 10 sxs cement.

STATE CORPORATION COMMISSION

Remarks: Allied Cement 60/40 6% gel MAY 03 1988 05-03-1988

(If additional description is necessary, use BACK of this form.)

Wichita, Kansas

INVOICED (If desired, observe this plugging.)

Signed Steve VanGieson (TECHNICIAN)

DATE 5-6-88

INV. NO. 20554

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date... 4 month 4 day 88 year

API Number 15-077-21,173-00-00

OPERATOR: License # 5123
Name: Pickrell Drilling Company, Inc.
Address: 110 N. Market, Suite 205
City/State/Zip: Wichita, KS 67202
Contact Person: Jay McNeil
Phone: 262-8427

NE SE Sec. 5 Twp. 31 S, Rg. 7 East West
1980 Ft. from South Line of Section
660 Ft. from East Line of Section

CONTRACTOR: License # 5123
Name: Company Tools
City/State:

(Note: Locate well on Section Plat on reverse side)
Nearest lease or unit boundary line ... 660 feet

Well Drilled For: Well Class: Type Equipment:
X Oil Storage Infield X Mud Rotary
X Gas Inj Pool Ext Air Rotary
OWWO Expt X Wildcat Cable

Lease Name: Burg Well # 1-B
Ground surface elevation ... 1585 feet MSL

If OWWO: old well info as follows:
Operator
Well Name
Comp Date Old Total Depth

Domestic well within 330 feet: yes X no
Municipal well within one mile: yes X no
Depth to bottom of fresh water ... 60'
Depth to bottom of usable water ... 150'

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.
Date 3-31-88 Signature of Operator or Agent Title Chief Geologist

Surface pipe by Alternate: 240+ feet 1 X 2
Surface pipe planned to be set
Conductor pipe required
Projected Total Depth ... 4550' feet
Formation ... Mississippian

For KCC Use:
Conductor Pipe Required ... feet; Minimum Surface Pipe Required ... feet per Alt. 1 X
This Authorization Expires 10-1-88 Approved By PCH 3-31-88

EFFECTIVE DATE: 4-5-88

NE SE Sec. 5 Twp. 31 S, Rg. 7 East West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

Table with 3 columns: Plug depth, Formation, and Feet of cement. Includes entries for 1st through 5th plugs and Rathole/Mousehole to surface minus 5 feet.

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging. In Addition: Call district office before well is either plugged or production casing is cemented in. (Call 7 a.m. to 5 p.m. workdays)

District office use only:
API #15-077-21,173
Surface casing of ... feet set with ... sxs at ... hours, ... 19
Alternate 1 or 2 surface pipe was used.
Alternate 2 cementing was completed @ ... ft. depth with ... sxs on ... 19
Hole plugged ... 19 agent